

Multi-Purpose Clamps

Swivel Clamps

Used to hold apparatus near the lab-frame. Unlike extension clamps, the swivel clamps have an integral holder for attaching to a lab-frame or other apparatus. Built-in holder grips rods up to 19mm (0.75") in diameter and is adjustable for forward or reverse-facing adjustment screws. Shaft wing-nut allows the holding angle of the swivel clamp to adjust through 360° of rotation and can be locked in place once desired position is achieved. Stainless steel electro-polished finish or nickel-plated zinc construction. Supplied with non-slip vinyl sleeves and, for temperatures above 100°C, fiberglass covers.

NOTE: Replacement vinyl and fiberglass sleeves are available, page 137.

916365
(shown in stainless steel)



916068
(shown in nickel-plated zinc)



Material	Description	Size	Min. to Max. Grip Size	Prong Width	Overall Length	Part Number
Stainless steel	2-Prong Single Adjust	Medium	0 to 76mm (0 to 3")	23mm (0.91")	163mm (6.42")	916366
Nickel-plated zinc	2-Prong Single Adjust	Medium	0 to 76mm (0 to 3")	23mm (0.91")	163mm (6.42")	916067
Nickel-plated zinc	2-Prong Single Adjust	Large	0 to 95mm (0 to 3.74")	23mm (0.91")	180mm (7.09")	916068
Stainless steel	3-Prong Dual Adjust	Medium	0 to 69mm (0 to 2.72")	20mm (0.79")	178mm (7.01")	916365
Nickel-plated zinc	3-Prong Dual Adjust	Medium	0 to 69mm (0 to 2.72")	20mm (0.79")	178mm (7.01")	916066

Fixed-Position Clamps

Used to hold apparatus near the lab-frame where no adjustment is required after set-up. Built-in holder grips rods up to 19mm (0.75") in diameter. Fixed-Position Clamps have an integral holder but can be rotated after attachment to a lab-frame or other apparatus. Available in 2-prong or 3-prong. Stainless steel electro-polished finish or nickel-plated zinc construction. Supplied with non-slip vinyl sleeves and, for temperatures above 100°C, fiberglass covers.

NOTE: Replacement vinyl and fiberglass sleeves are available, page 137.

916369
(shown in stainless steel)



916070
(shown in nickel-plated zinc)



Material	Description	Size	Min. to Max. Grip Size	Prong Width	Overall Length	Part Number
Stainless steel	2-Prong Single Adjust	Medium	0 to 77mm (0 to 3.03")	23mm (0.91")	133mm (5.24")	916373
Nickel-plated zinc	2-Prong Single Adjust	Medium	0 to 77mm (0 to 3.03")	23mm (0.91")	133mm (5.24")	916070
Stainless steel	3-Prong Dual Adjust	Medium	0 to 69mm (0 to 2.72")	20mm (0.79")	146mm (5.75")	916369
Nickel-plated zinc	3-Prong Dual Adjust	Medium	0 to 69mm (0 to 2.72")	20mm (0.79")	146mm (5.75")	916069

Double Jaw Utility Clamp

Swivels 360° and locks securely in desired position. These 2-prong clamps have a medium and a large clamp on each end. Nickel-plated zinc construction. Supplied with non-slip vinyl sleeves and, for temperatures above 100°C, fiberglass covers.

NOTE: Replacement vinyl and fiberglass sleeves are available, page 137.



916073

Description	Min. to Max. Grip Size	Prong Width	Overall Length	Part Number
Medium 2-Prong	0 to 76mm (0 to 3")	23mm (0.91")	222mm (8.74")	916073
Large 2-Prong	0 to 95mm (0 to 3.74")	23mm (0.91")	222mm (8.74")	916073