

### Specifications

**Load Cell, NTEP Certified:**

IP69K stainless steel and hermetically sealed

**Output Impedance:**

350

**Maximum Overload:**

180 to 200% depending on capacity

**Overload Protection:**

Five-point, independently adjusted

**Cable Length:**

34 in or 10 ft

**Compensated Temperature Range:**

14° F to 104° F (-10° C to 40° C)

**Approvals:**

NTEP CC 95-072, Class III 5,000 d

Measurement Canada AM-5082, Class III 5,000 d

Load cell is FM approved

**Warranty:**

Three-year limited warranty (includes water ingress)



### Standard Features

- 304 stainless steel construction
- Meets HACCP requirements
- Five-point overload protection
- Specially designed adjustable support feet provide exceptional traction and will not scratch surfaces
- IP69K, stainless steel hermetically sealed load cell

### APPROVALS



### Part Number/Price

| Part #             | Platform Capacity      | Dimensions        | Est. Weight | Price      |
|--------------------|------------------------|-------------------|-------------|------------|
| <b>10 ft Cable</b> | <b>34 in Cable</b>     |                   |             |            |
| 112600             | 106143 5 lb (2.5 kg)   | 10 x 10 x 4.25 in | 14 lb       | \$1,090.00 |
| 112602             | 106144 10 lb (5 kg)    | 10 x 10 x 4.25 in | 14 lb       | \$1,090.00 |
| 112604             | 106145 25 lb (12.5 kg) | 10 x 10 x 4.25 in | 14 lb       | \$1,090.00 |
| 112606             | 106146 25 lb (12.5 kg) | 12 x 12 x 4.25 in | 17 lb       | \$1,170.00 |
| 112608             | 106147 50 lb (25 kg)   | 12 x 12 x 4.25 in | 17 lb       | \$1,170.00 |
| 112610             | 106148 100 lb (50 kg)  | 12 x 12 x 4.25 in | 17 lb       | \$1,170.00 |

### Options/Accessories

| Part #  | Description  | Price                          |
|---------|--|--------------------------------|
| Consult | Columns, Ball Transfer Tops, Roller Conveyor Tops, Carts available | See end of section for details |

| Drawing Dimensions   |                      |    |                      |
|----------------------|----------------------|----|----------------------|
| <b>10 in x 10 in</b> |                      |    |                      |
| A                    | 4.25 in (107.95 mm)  | C  | 10 in (254 mm)       |
| B                    | 10 in (254 mm)       | C1 | 10.25 in (260.35 mm) |
| B1                   | 10.25 in (260.35 mm) |    |                      |
| <b>12 in x 12 in</b> |                      |    |                      |
| A                    | 4.25 in (107.95 mm)  | C  | 12.0 in (304.8 mm)   |
| B                    | 12.0 in (304.8 mm)   | C1 | 12.25 (311.15 mm)    |
| B1                   | 12.25 (311.15 mm)    |    |                      |

