

Specifications

	GF-20K	GF-30K	GF-32K	
Part#	97796	97797	97798	
List Price	\$3,240.00	\$3,800.00	\$2,880.00	
Capacity	21 kg	31 kg	6.1/31 kg	
Resolution	0.1 g	0.1 g	0.1/1 g	
Operating Modes	Counting, Percentage			
Linearity	±0.2g ±1 g/0.2g		±1 g/0.2 g	
Stabilization time	Approx. 1.5 seconds (typical in FAST mode)			
Repeatability	0.1 g		0.5 g/0.1 g	
Sensitivity Drift (10° C to 30° C)	±3 ppm/° C		±5 ppm/° C	
Display refresh	5 times per second/10 times per second			
Operating Temperature	41° F to 104° F (5° C to 40° C) RH less than 85% (No condensation)			
Pan Size (W x D)	Stainless steel 10.62 x 8.26 in (270 x 210 mm)			
Dimensions	(W x D x H) 11.81 x 13.98 x 4.37 in (300 x 355 x 111 mm)			
Weight	18.3 lb (8.3 kg)			
External Cal. Mass	10, 20 kg		20, 30 kg	
Power	120/240 VAC adapter			
Warranty	Five-year Limited Warranty			
Return Policy	A&D Weighing Standard Policy - restock fee may apply			
Decimal Ounces	740.755 x 0.005 oz	1,093.495 x 0.005 oz	1,093.50 x 0.05/215.170 x 0.005 oz	
Troy Ounce Pennyweight Carat	675.165 x 0.005 ozt	996.675 x 0.005 ozt	996.65 x 0.05/196.120 x 0.005 ozt	
Pennyweight	13,503.3 x 0.1 dwt	19,933.5 x 0.1 dwt	19,933 x 1/3,922.4 x 0.1 dwt	
Carat	105,000.0 x 0.5 ct	155,000.0 x 0.5 ct	155,000 x 5/30,500.0 x 0.5 ct	
Momme	5,600.00 x 0.05 mom	8,266.65 x 0.05 mom	8,266.5 x 0.5/1,626.65 x 0.05 mom	
Grain	324,080 x 2 GN	478,404 x 2 GN	N/A	
	46.2970 x 0.0005 lb	68.3435 x 0.0005 lb	68.345 x 0.005/13.4480 x 0.0005 lb	
Pound/Ounce	46 lb x 0.01 oz	68 lb x 0.01 oz	68 lb x 0.1 oz/17 lb x 0.01 oz	

Part Number/Price

Part#	Model#	Description	Price
97792	GF-8K2	2.1 kg/8.1 kg x 0.01 g/0.1 g	\$2,860.00
97793	GF-8K	8.1 kg x 0.01 g	\$3,375.00
97794	GF-10K	10.1 kg x 0.01 g	\$3,600.00
97795	GF-12K	12kg x 0.1 g	\$3,035.00
97796	GF-20K	21 kg x 0.1 g	\$3,240.00
97797	GF-30K	31 kg x 0.1 g	\$3,800.00
97798	GF-32K	31 kg/6.1 kg x 1 g/0.1 g	\$2,880.00

Options/Accessories

Part#	A&D Model#	Description	Price
97782	GX-04K*	Comparator/output and RS-232C/20 mA interface	\$373.00
97783	GX-06K*	Analog output/20 mA interface	\$857.00
97784	GX-07K**	Waterproof cable for standard RS-232C	\$317.00
102899	GXK-12	Animal weighing pan	\$852.00
102898	GXK-31	Draft shield	\$118.00
97605	AD-100-2	Anti-theft device	\$75.00
97785	AX:073007197A	Protective in-use cover	\$21.00
97649	TB:648	AC adapter (120 V/220 V)	\$44.00
151247	AD-1688	Data logger	\$311.00
196128	AD-8127	Impact dot matrix, statistical printer, includes cable	\$869.00

^{*}GX-04K, GX-06K, replace standard RS-232C and cannot be used at the same time. IP65 rating does not apply when the GX-04K or the GX-06K is installed.

^{**}Use the GX-07K optional waterproof RS-232C cable, in order to use the standard RS-232 interface for water and dust proof (IP65).

Weigh Out/Printer Kiosk Automated Truck Scale System



Standard Features

Weigh Out/Printer Kiosk

- 920i® HMI with sun shield
- Six serial ports
- 1 MB database memory
- Two additional expansion slots
- · Slide door access to ticket
- 8 in paper roll
- · Operator prompting
- Formatable tickets
- · Transmits weight to remote display
- Stop/Go remote display traffic light control
- · Direct thermal kiosk printer

Weigh Out/Printer Kiosk Options:

- Ethernet TCP/IP (wired and WiFi options available)
- Single or dual channel A/D cards
- RFID reader
- Currency accepter (U.S. currency only)
- Internal heater
- · Gate control
- · Loop detector output
- · Automated traffic light control

Consult for the following options:

- Stainless steel enclosure
- Bar code badge scanner
- 230 VAC

