# talboys

## LABORATORY EQUIPMENT CATALOG

### Multi-Purpose Clamps

#### **UltraJaws Heavy-Duty Clamps**

- Large grip adjustment range
- Single or dual adjust
- Available in three sizes; small, medium, and large
- Nickel-plated zinc

Talboys patented multi-purpose UltraJaws Heavy-Duty Clamps feature an innovative closed yoke construction that minimizes contamination and corrosion of internal components. The unique design enables secure gripping and positioning with added strength and durability.


Available in both single and dual prong adjustment, prongs open gradually to maximize grip size without binding. Both designs feature precise pressure regulation when gripping glassware surfaces to reduce the chance of breakage. UltraJaws clamps are constructed with extension rods for easy attachment to lab-frames and other apparatus. Supplied with non-slip vinyl sleeves and, for temperatures above 100°C, fiberglass covers.

The prong height of the UltraJaws Heavy-Duty Clamps make them ideal for use in holding and securing glassware with precision ground glass joints. The chart details which UltraJaws Clamps are recommended.

**NOTE:** An additional holder must be purchased in order to attach clamps to frames or other apparatus.

See the Connectors & Holders section of this catalog, pages 138-140.

Replacement vinyl and fiberglass sleeves are available, page 137.



GROUND GLASS JOINT F	REFERENCE CHART
Clamp	Joint Size
Small Dual Adjust	10/30, 12/30, 14/20, 19/22, 24/40, 29/42, 34/45
Medium Dual Adjust	14/40, 19/38
Large Dual Adjust	45/50

#### Single Adjust Clamps



916109



Size	(A) Min. to Max Grip Size	(B) Prong Width	(C) Arm Length	(D) Arm Dia.	(E) Overall Length	Part Numbe
Small	0 to 23mm (0 to 0.91")	6mm (0.24")	102mm (4")	8mm (0.32")	162mm (6.38")	916114
Medium	0 to 50mm (0 to 1.97")	19mm (0.75")	127mm (5")	11mm (0.43")	229mm (9.02")	916112
Large	0 to 72mm (0 to 2.83")	29mm (1.14")	127mm (5")	11mm (0.43")	260mm (10.24")	916110
Ū.	ual Adjust Clamps				· · ·	
3-Prong D	ual Adjust Clamps			(D) Arm Dia.	(E) Overall Lenath	Part Numbe
3-Prong D Size		(B) Prong Width 6mm (0.24")	(C) Arm Length	(D) Arm Dia. 8mm (0.32")	(E) Overall Length 152mm (5.98")	<b>Part Numbe</b> 916113
Ū.	(A) Min. to Max Grip Size	(B) Prong Width	(C) Arm Length		.,	<b>Part Numbe</b> 916113 916111

142