

Practum/Quintix/Secura

Precision Balances

Part Number/Price

Part Number	Model	Description	Price
153987	Practum 612-1S	610 g x 0.01 g	\$1,155.00
153998	Quintix 612-1S	610 g x 0.01 g	\$1,810.00
153988	Practum 1102-1S	1,100 g x 0.01 g	\$1,275.00
153999	Quintix 1102-1S	1,100 g x 0.01 g	\$2,050.00
154010	Secura 1102-1S	1,100 g x 0.01 g	\$2,340.00
153989	Practum 2102-1S	2,110 g x 0.01 g	\$1,335.00
154000	Quintix 2102-1S	2,110 g x 0.01 g	\$2,290.00
154011	Secura 2102-1S	2,110 g x 0.01 g	\$2,785.00
154001	Quintix 3102-1S	3,100 g x 0.01 g	\$2,535.00
154012	Secura 3102-1S	3,100 g x 0.01 g	\$3,010.00
154003	Quintix 5102-1S	5,100 g x 0.01 g	\$3,140.00
154013	Secura 5102-1S	5,100 g x 0.01 g	\$3,460.00
153991	Practum 5101-1S	5,100 g x 0.1 g	\$1,360.00
154004	Quintix 5101-1S	5,100 g x 0.1 g	\$1,810.00
153990	Practum 5100-1S	5,100 g x 1.0 g	\$1,050.00
154002	Quintix 5100-1S	5,100 g x 1.0 g	\$1,450.00

Options/Accessories

Part #	Model #	Description	Price
191429	6971790	AC adapter, 110-240V, six power plugs	\$78.00
155847	YCC03-D09	Adapter cable, USB to RS-232	\$59.00

Entris II Basic Essential

Analytical/Precision/Toploading Balances

Capacity: 60g-8,200g Readability: 0.0001-1.0g

Standard Features

- User-friendly operation
- Basic applications
- Monolithic weighing systems
- Aluminum die-cast base, ABS housing
- Front level bubble
- RS-232 standard
- Below balance weighing



Specifications

	BCE64I-1S [^]	BCE124I-1S [^]	BCE224I-1S [^]	BCE223I-1S [^]	BCE323I-1S [^]	BCE423I-1S [^]	BCE623I-1S [^]
Part#	197392	197393	197394	197395	197396	197397	197398
List Price	\$2,290.00	\$2,600.00	\$2,910.00	\$1,455.00	\$1,665.00	\$2,080.00	\$2,290.00
Capacity	60g	120g	220g	220g	320g	420g	620g
Readability	0.1 mg	0.1 mg	0.1 mg	0.001 g	0.001 g	0.001 g	0.001 g
Repeatability	±0.1 mg	±0.1 mg	±0.1 mg	±1 mg	±1 mg	±1 mg	±1 mg
Linearity	±0.2 mg	±0.2 mg	±0.2 mg	±2 mg	±2 mg	±2 mg	±2 mg
External Calibration Weight	50g	100g	200g	200g	200g	200g	500g
Weighing Modes	Gram, Kilogram, Carat, Pound, Ounce, Troy Ounce, Hong Kong Tael, Singapore Tael, Taiwan Tael, Grain, Pennyweights, Milligram, Parts per Pound, China Teal, Mommies, Austrian Carat, Tola, Baht, Mesghal, Tons, Pounds:Ounces, Newton						
Applications	Weighing, Density, Percentage, Counting, Mass Unit Conversion						
Display Type	Backlit LCD white, 15 mm digits						
Operating Humidity	15% to 80% for temperatures up to 31° C						
Operating Temperature	41° F to 104° F (5° C to 40° C)						
Stabilization Time (typical)	2.5 seconds		1.3 seconds		1.1 seconds		1.0 seconds
Net Weight (kg/lbs)	6.2kg (13.7 lb)						
Pan Size/Type	90 mm (3.5in) diameter pan, stainless steel			120 mm (4.7 in) pan, stainless steel			
Dimensions (W x D x H)	230 x 303 x 330 mm (9.1 x 11.9 x 13 in)			230 x 303 x 136 mm (9.1 x 11.9 x 5.4 in)			
AC Power Requirements	AC adapter, 115V-240V, US plug						
Warranty	Two-year Limited Warranty						

[^]Weighing Chamber

Specifications

	BCE622I-1S	BCE653I-1S [^]	BCE822II-1S	BCE1202I-1S	BCE2202I-1S	BCE2201I-1S	BCE3202I-1S
Part#	197399	197400	197401	197402	197403	197404	197405
List Price	\$1,350.00	\$2,495.00	\$1,455.00	\$1,560.00	\$1,665.00	\$1,455.00	\$1,770.00
Capacity	620g	650g	820g	1,200g	2,200g	2,200g	3,200g
Readability	0.01g	0.001g	0.01g	0.01g	0.01g	0.1g	0.01g
Repeatability	±1 mg	±1 mg	±1 mg	±1 mg	±1 mg	±0.1g	±0.1g
Linearity	±2 mg	±2 mg	±2 mg	±2 mg	±2 mg	±0.3g	±0.3g
External Calibration Weight	500g	500g	500g	500g	500g	2,000g	5,000g
Weighing Modes	Gram, Kilogram, Carat, Pound, Ounce, Troy Ounce, Hong Kong Tael, Singapore Tael, Taiwan Tael, Grain, Pennyweights, Milligram, Parts per Pound, China Teal, Mommies, Austrian Carat, Tola, Baht, Mesghal, Tons, Pounds:Ounces, Newton						
Applications	Weighing, Density, Percentage, Counting, Mass Unit Conversion						
Display Type	Backlit LCD white, 15 mm digits						
Operating Humidity	15% to 80% for temperatures up to 31° C						
Operating Temperature	41° F to 104° F (5° C to 40° C)						
Stabilization Time (typical)	1.0 seconds		1.5 seconds				
Net Weight (kg/lb)	6.3 kg (13.9 lb)		4.8 kg (10.6 lb)	5.4 kg (12 lb)	6.3 kg (13.9 lb)	5.4 kg (12 lb)	5.4 kg (12 lb)
Pan Size/Type	120 mm (4.7 in) pan, stainless steel						
Dimensions (W x D x H)	230 x 303 x 330 mm (9.1 x 11.9 x 13 in)		230 x 303 x 87 mm (9.1 x 11.9 x 3.4 in)		(W x D x H) 230 x 303 x 136 mm (9.1 x 11.9 x 5.4 in)		
AC Power Requirements	AC adapter, 115V-240V, US plug						
Warranty	Two-year Limited Warranty						