

## Part Number/Price

Part #	Model #	Description	Price
121195	EX223^	220 g x 0.001 g	\$2,718.00
121196	EX423^	420 g x 0.001 g	\$3,180.00
121197	EX623^	620 g x 0.001 g	\$3,889.00
121198	EX1103^	1,100 g x 0.001 g	\$4,565.00
121199	EX2202	2,200 g x 0.01 g	\$2,945.00
121200	EX4202	4,200 g x 0.01 g	\$3,385.00
121201	EX6202	6,200 g x 0.01 g	\$3,841.00
121202	EX10202	10,200 g x 0.01 g	\$4,560.00
121203	EX6201	6,200 g x 0.1 g	\$3,190.00
121204	EX10201	10,200 g x 0.1 g	\$3,500.00

^Weighing Chamber

## Options/Accessories

Part #	Model #	Description	Price
67422	80253384	Density determination kit (for 410 g capacity and below)	\$656.00
35263	80850043	Security device for EX	\$226.00
77712	80500524	RS-232 cable, PC 25-pin to EX	\$188.00
70406	80500525	RS-232 cable, PC nine-pin to EX	\$188.00
156234	46001724	Multi-range AC adapter	\$43.00
156235	46001780	International plug set	\$17.00



**Standard Features**

- Touchless IR (infrared) sensors minimize keypad use
- Program IR sensor to control operations including print, tare and other selectable functions
- Color VGA, 5.7-in display with icons for simple menu navigation
- Multiple application modes designed for versatility
- AutoCal™ Calibration
- Robust IP 54 die-cast metal bottom housing with stainless steel pan
- Integral weigh below hook
- ENERGY STAR qualified adapter

**APPROVALS**



**Specifications**

	Ex12001	Ex24001	Ex35001
Part#	157235	157236	157237
List Price	\$3,872.00	\$4,717.00	\$5,540.00
Capacity	12,000g	24,000g	35,000g
Resolution	0.1 g		
Weighing Modes	Gram, Kilogram, Carat, Ounce, Troy Ounce, Pound., Pennyweight, Mommies, Grain, Tical, Tola, Newton, Mesghal, 3 Custom Units		
Operating Modes	Weighing, Counting, Animal/Dynamic Weighing, Checkweighing, Percent Weighing, Filling, Parts Counting, Totalization, Formulation, Differential Weighing, Density Determination, Peak Hold, Ingredient Costing, SQC		
Repeatability	±0.1 g		
Linearity	±0.2 g		
Stabilization Time	≤1 seconds		
Operating Temperature	14° F to 140° F (-10° C to 60° C)		
Pan Size	14.84 x 12.24 in (377 x 311 mm)		
Display Housing Dimensions	(W x D x H) 7.7 x 3.5 x 6.0 in (195 x 90 x 154 mm)		
Dimensions Base	(W x D x H) 14.84 x 4.72 x 17.44 in (377 x 120 x 443 mm)		
Weight (Approx.)	25 lb (12.5 kg)		
Calibration	Auto Cal internal calibration		
Power	AC adapter input: 100-240VAC 0.6A 50-60 Hz		
Warranty	Two-year Limited Warranty		
Return Policy	OHAUS Standard Policy - restock fee may apply		
Approvals	Measurement Canada AM-5957		