

Part Number/Price

Part #	Model #	Description	Price
108156	TS-620	620 g x 0.01 g	\$1,365.00
108157	TS-6200	6,200 g x 0.1 g	\$1,475.00
112182	TS-8200	8,200 g x 0.1 g	\$1,550.00

Options/Accessories

Part #	Description	Price
108499	AC adapter, multi-range 110:230 VAC, 6VDC	\$52.00
72440	Nine-pin D-sub F-25-Pin D-sub connector	\$67.00
22436	Nine-pin D-sub F to blunt end	\$67.00
66535	Null modem cable	\$46.00
119064	Slimline adapter, null modem gender changer	\$11.00
109236	Under weigh hook	\$27.00
109238	Waterproof RS-232 cable	\$360.00
109050	Additional operating manual	\$16.00
112611	Battery operator manual	\$6.00
112516	Battery holder option, requires 4 AA batteries (not included)	\$105.00
119919	AbleCable, requires null modem cable PN 66535	\$190.00



Standard Features

- Anti-electrostatic 360° transparent windshield
- Eight-digit, 16.5 mm-high liquid crystal display (LCD) with backlight
- Single-touch response setting for environment
- 40-step bar graph display
- RS-232C interface
- ISO/GLP/GMP compliant printing record
- Underweigh hook included
- Internal calibration
- Plastic housing

Specifications

	TA Plus-124 [^]	TA Plus-224 [^]	
Part #	196569	196570	
List Price	\$2,035.00	\$2,055.00	
Capacity	120g	220g	
Resolution	0.0001 g	0.0001 g	
Operating Modes	Counting, Percentage, Limit Function (Checkweighing), Specific Gravity		
Repeatability	1 division		
Linearity	1 division		
Operating Temperature	50° F to 86° F (10° C to 30° C) 80% RH or lower		
RS232 Specifications	Baud rate - 1200/2400/4800/9600/19200 bps, 8/7 data bits, Parity bit-None/Odd/Even		
Pan Size	Ø 3.15 in (80 mm)		
Dimensions	11 x 7.9 x 12 in (290 x 200 x 306 mm)		
Weight (Approx.)	6.4 lb (2.9 kg)		
Calibration Weight	120g	220g	
Power	120 VAC adapter		
Warranty	Five-year Limited Warranty		
Return Policy	Rice Lake Standard Policy		
UNIT OF MEASURE	Decimal Ounce	4.2 x 0.000005 oz	7.7 x 0.000005 oz
	Decimal Pound	0.26 x 0.000001 lb	0.48 x 0.000001 lb
	Troy Ounce	3.8 x 0.000005 ozt	7 x 0.000005 ozt
	Pennyweight	77 x 0.0001 dwt	140 x 0.0001 dwt
	Carat	600 x 0.0005 ct	1100 x 0.001 ct
	Momme	32 x 0.00005 mom	58 x 0.00005 mom
	Grain Unit	1,800 x 0.002 GN	3,300 x 0.002 GN
	Tael	3.2 x 0.000005 TL	5.8 x 0.000005 TL
	Tola	10 x 0.00001 to	18 x 0.00001 to

[^] Weighing Chamber