

## Part Number/Price

Part#	Model#	Description	Price
33350	710-00	610 g x 0.1 g	\$281.00
33351	710-T0	610 g x 0.1 g	\$343.00
33352	720-00	610 g x 0.1 g	\$331.00
33355	750-S0	610 g x 0.1 g	\$155.00
33357	760-00	610 g x 0.1 g	\$290.00
33353	720-S0	610 g x 0.1 g	\$384.00
33354	730-00	610 g/2,610 g x 0.1 g	\$414.00
33361	1650-00	610 g x 0.1 g	\$363.00
33362	1650-W0	2,610 g x 0.1 g	\$420.00
33360	1610-00	610 g x 0.1 g	\$420.00
103109	TP2611	2,610 g x 0.1 g	\$223.00

## **Options/Accessories**

Part#	Model#	Description	Price
33417	80780011	Rod and clamp assembly	\$72.00
33446	80780014	Polypropylene scoop, 12 x 6 x 2.75 in (304 x 152 x 70 mm) footed and counterweighted for balance without tare	\$54.00
33447	80780015	Stainless steel scoop, 12 x 6 x 2.75 in (304 x 152 x 70 mm) footed and counterweighted for balance without tare	\$127.00
33448	80780016	Polypropylene Maxi-Scoop®, 10 in (254 mm) dia. x 2.5 in (70 mm) deep with pouring spout and counterweight	\$57.00
33463	80780017	Vinyl dust cover	\$39.00
33414	80780108	Attachment weight set, metric	\$70.00



## **Standard Features**


Capacity: 6lb-30lb

**APPROVALS** 

· Designed for food service and other industrial applications with a focus on speed, durability and cleanliness

Readability: 0.0002lb-0.01lb

- · All stainless steel, high-quality formed construction for sanitary cleaning and durability
- · Checkweighing function for food packaging and preparation
- Internal rechargeable battery assures excellent portability
- Stainless steel housing and pan with non-slip rubber feet
- · Checkweighing mode with 3-LED indicator and audible alarm
- · Bright backlit LCD display
- · Stable weight display within 2 seconds
- · Multiple weighing units: lb, decimal/fractional oz, kg, g and lb
- · AC power or internal rechargeable lead acid battery
- NSF-certified, USDA-AMS accepted, supports HACCP compliance
- EC/OIML type approved





## **Specifications**

оросиновноги									
	FD3H	FD3	FD6H	FD6	FD15H	FD15			
Part#	102774	-	102775	-	102776	-			
List Price	\$951.00	-	\$951.00	-	\$951.00				
Part#	-	87824	-	87825	-	87826			
List Price		\$848.00		\$848.00	-	\$848.00			
Approvals	NSF Ii	NSF listed/Certified to NSF C-2, UL C-US listed, NTEP CC 05-072 Class III, Measurement Canada AM-5582							
Capacity	6 lb	6 lb	15 lb	15 lb	30 lb	30 lb			
Resolution	0.0002 lb	0.002 lb	0.001 lb	0.005 lb	0.001 lb	0.01 lb			
Overload capacity		150%							
Operating Modes		Weighing, Checkweighing							
Repeatability	0.:	0.2g 0.4g		2 g					
Linearity	±0	±0.2g ±0.4g			±0.2 g				
Stabilization Time		< 2 seconds							
Operating Temperature	ting Temperature 14° F to 104° F (-10° C to 40° C) 10% to 85% relative humidity, non-condensing								
Environmental		IP43							
Pan Size			8.2 x 8.2 in (2	09 x 209 mm)					
Dimensions		(W x D x H) 9 x 12 x 2.8 in (300 x 223 x 71 mm)							
Weight (Approx.)		8 lb (3.6 kg)							
Est. Ship Weight		11 lb (5 kg)							
Power	120V AC adapter, 9V DC 0.5A 50/60 Hz (Other adapters available by special request)								
Battery life			***************************************	120 hours					
Warranty One-year Limited Warranty									
Return Policy		OHAUS Standard Policy - restock fee may apply							
₩ Kilogram	3 x 0.0001 kg	3 x 0.001 kg	6 x 0.0002 kg	6 x 0.002 kg	15 x 0.005 kg	15 x 0.005 kg			
Grams	3,000 x .1 g	3,000 x 1 g	6,000 x 0.2 g	6,000 x 2 g	-	15,000 x 5 g			
Grams Ounce	96 oz x 0.005 oz; 96 oz x 1/4 oz	96 oz x 0.05 oz or 1/4 oz	240 oz x 0.01 oz; 240 oz x 1/4 oz	240 oz x 0.1 oz or 1/4 oz	480 oz x 0.02 oz or 1/4 oz	480 oz x 0.2 oz or 1/4 oz			
Pound x Ounce	6 lb 0 oz x 1/4 oz; 6 lb 0 oz x 0.1 oz	-	15 lb 0 oz x 0.1 oz; 15 lb 0 oz x 1/4 oz	-	30 lb 0 oz x 0.1 oz or 1/4 oz	-			