

### Part Number/Price

Part #	Model #	Capacity	Est. Weight	Price
165338	EQ-300	300 g x 0.01 g	6 lb	\$305.00
165339	EQ-600	600 g x 0.02 g	6 lb	\$305.00
165340	EQ-1500	1,500 g x 0.05 g	6 lb	\$305.00
165341	EQ-3000	3,000 g x 0.1 g	6 lb	\$305.00
165342	EQ-6000	6,000 g x 0.2 g	6 lb	\$305.00

### Options/Accessories

Part #	Description	Price
41279	Printer cable, DB9M to 25-Pin M	\$67.00
103141	SP712 dot matrix printer, tear bar	\$350.00
119919	AbleCable RS-232/USB cable (requires 130789)	\$190.00
130789	Slim line null modem adapter	\$13.00
131135	Aluminum case	\$103.00
165183	AC adapter, 110-240 VAC, interchangeable plugs	\$46.00



PN 165183 Multi-range AC adapter and multi-plug

# TE Series

Tuning Fork Enhanced Balance

Capacity: 620g - 15kg    Readability: 0.001g - 0.1g



## Standard Features

- External weight calibration
- Seven-segment (main)/16-segment (sub) display
- Selectable modes: Weighing, Counting, Percentage, Coefficient, Specific Gravity, Statistics, Animal and Formulation
- Mono-metal tuning fork technology (MMTF) provides quick response and stability
- 30-step bar graph display
- 100-240 VAC adapter included
- AA dry-cell port, (150 hours continuous use with LCD backlight and communication signal ON)
- RS-232 and USB
- Glass breeze break (TE-223 and TE-623 only)
- NTEP Certified (COC 17-104)

## APPROVALS



## Specifications

	TE-223 <sup>^</sup>	TE-623 <sup>^</sup>	TE-3202	TE-6202	TE-15001	
Part#	187600	186030	186035	186036	186037	
List Price	\$1,082.00	\$1,422.00	\$1,180.00	\$1,450.00	\$1,135.00	
Capacity	220 g	620 g	3,200 g	6,200 g	15,000 g	
Resolution	0.001 g	0.001 g	0.01 g	0.01 g	0.1 g	
NTEP Resolution	0.01 g	0.01 g	0.1 g	0.1 g	1.0 g	
Operating Modes	Weighing, Counting, Percentage, Coefficient, Specific Gravity, Statistics, Animal, Formulation					
Repeatability	1 division					
Linearity	1 division					
Operating Temperature	41° F to 95° F (5° C to 35° C)					
Pan Size	4.6 in (118 mm)		6.3 in x 7.1 in (160 mm x 180 mm)			
Dimensions	10.6 in x 8.1 in x 11.8 in (270 mm x 208 mm x 301 mm)		10.4 in x 7.5 in x 3.4 in (265 mm x 191.5 mm x 86 mm)			
RS-232 Specifications	Baud Rate 1200, 2400, 480, 9600, 19200, 38400, 57600, 115200bps					
Est. Ship Weight	6.5 lb (3 kg)		6.0 lb (2.7 kg)			
Power	100-240VAC adapter, AA dry cell (batteries not included)					
Approvals	NTEP CC 17-104					
Warranty	Five-year Limited Warranty					
Return Policy	Rice Lake Standard Policy					
UNIT OF MEASURE	Gram	220 x 0.001 g	620 x 0.001 g	3,200 x 0.01 g	6,200 x 0.01 g	15,000 x 0.1 g
	Carat	1,100 x 0.01 ct	3,100 x 0.01 ct	16,000 x 0.1 ct	31,000 x 0.1 ct	75,000 x 1 g
	Pound	0.48 x 0.00001 lb	1.3 x 0.00001 lb	7 x 0.0001 lb	13 x 0.0001 lb	33 x 0.001 lb
	Ounce	7.7 x 0.0001 oz	21 x 0.0001 oz	110 x 0.001 oz	210 x 0.001 oz	520 x 0.01 oz
	Troy Ounce	7 x 0.0001 ozt	19 x 0.0001 ozt	100 x 0.001 ozt	190 x 0.001 ozt	480 x 0.01 ozt
	Grain	3,300 x 0.1 GN	9,500 x 0.1 GN	49,000 x 1 GN	95,000 x 1 GN	230,000 x 10 GN
	Pennyweight	140 x 0.001 dwt	390 x 0.001 dwt	2,000 x 0.01 dwt	3,900 x 0.01 dwt	9,600 x 0.1 dwt
	Momme	58 x 0.001 mom	160 x 0.001 mom	850 x 0.01 mom	1,600 x 0.01 mom	4,000 x 0.1 mom
	MSG	47 x 0.001 MSG	130 x 0.001 MSG	690 x 0.01 MSG	1,300 x 0.01 MSG	3,200 x 0.1 MSG
	Tael (Hong Kong)	5.8 x 0.0001 TL	16 x 0.0001 TL	85 x 0.001 TL	160 x 0.001 TL	400 x 0.01 TL
	Tael (Singapore)	5.8 x 0.0001 TL	16 x 0.0001 TL	84 x 0.001 TL	160 x 0.001 TL	390 x 0.01 TL
	Tael (Taiwan)	5.8 x 0.0001 TL	16 x 0.0001 TL	85 x 0.001 TL	160 x 0.001 TL	400 x 0.01 TL
	Tola	18 x 0.0001 to	53 x 0.0001 to	270 x 0.001 to	530 x 0.001 to	1,200 x 0.01 to
	Bat	14 x 0.0001 Bat	40 x 0.0001 Bat	210 x 0.001 Bat	400 x 0.001 Bat	980 x 0.01 Bat
	Milligrams	220,000 x 1 mg	620,000 x 1 mg	3,200,000 x 10 mg	6,200,000 x 10 mg	15,000,000 x 100 mg

<sup>^</sup>Weighing Chamber