

## Specifications

### Dimensions:

9.1 in x 9.1 in x 2.75 in  
(23.1 cm x 23.1 cm x 7.0 cm)

### Color:

Black

### Housing Material:

UL94 Polycarbonate

### Mounting:

Drill mounting box to meet application  
Drill points provided for US and EU wall  
boxes, and 75 mm, 100 mm and 200 mm  
VESA mounts

### Storage Temperature:

-67° F to 185° F (-55° C to 85° C)

### Operating Temperature:

-30° F to 150° F (-35° C to 65° C)

### Operating Humidity:

5% to 95% relative humidity non-condensing

### Rating:

IP65

### Typical Maximum Read Range:

9.8 - 16.4 feet  
(3 - 5 meters) (Mexico)

### Transmit Frequency:

865-868 MHz/902-928 MHz  
dependent on regional regulations

### Approvals:

UL 294/cUL, CB Scheme, FCC Certification,  
IC (Canada),  
CE (Europe), IFETEL (Mexico)



## Standard Features

- Discreet hands-free authentication solution for long range parking and gate control
- Discreet hands-free authentication solution for long range truck identification
- IP65 rating allows outdoor mounting
- Supports Wiegand standards
- Requires Wiegand converter, consult with a sales engineer with application specifics

## Part Number/Price

Part #	Description	Price
184458	Reader, Long Range HID	\$1,595.00
184459	UHF Credentials (Factory programming required)	\$14.00
184466	Windshield Mount	\$10.00