CARBIDE GRIT HOLE SAWS

OVERVIEW

MILWAUKEE® Carbide Grit Hole Saws are designed for cutting abrasive materials such as brick, block, cement board, fiberglass and tile. Use a Carbide Tipped Pilot Bit (49-56-8005) when cutting ceramic tile, brick, and other abrasive materials.

FEATURES

- Tungsten Carbide Grit Edge for abrasive materials
- O Coarse Grit and Segmented Edge for fast cutting
- O Wide, Angled and Offset Slots for easy plug access



CARBIDE GRIT HOLE SAWS

Size	Part No.
3/4"	49-56-0405
7/8"	49-56-0409
1"	49-56-0413
1-1/8"	49-56-0417
1-1/4"	49-56-0422

Size	Part No.
1-3/8"	49-56-0426
1-3/4"	49-56-0437
2"	49-56-0444
2-1/4"	49-56-0449
2-1/2"	49-56-0456

RECESSED LIGHT HOLE CUTTERS - ADJUSTABLE

OVERVIEW

The MILWAUKEE® Adjustable Hole Cutter offers a one-size-fits-all solution to make holes in drywall and ceiling tile. Cutting diameters range from 2" through 7" with 1/4" increments for almost double the amount of sizes over the competition. Utilizing a QUIK-LOK™ Arbor for tool-free adjustability as well as laser-etched markings and size indicator, users can quickly and easily identify and change sizes without the use of a hex key. A best-in-class durable and reusable debris shield with spring collar keeps cutting blades level and work areas clean, especially in overhead cutting applications. Choose the Adjustable Hole Cutter for applications in drywall and ceiling tiles including: recessed lights, audio speakers, fire/security systems, and clearance holes.



FEATURES

- QUIK-LOK[™] Arbor for quick and easy tool-free adjustability
- 2" through 7" Diameters with 1/4" increments for a greater size range
- O Black Oxide Coated with laser-etched size indicators

RECESSED LIGHT HOLE CUTTERS - ADJUSTABLE

Description	Part No.
Adjustable Hole Cutter	49-56-0320
Adjustable Hole Cutter Replacement Blades and Pilot Bit	49-56-0290

RECESSED LIGHT HOLE SAWS - CONTINUOUS GRIT

OVERVIEW

MILWAUKEE® Recessed Light Hole Saws are manufactured using carbide grit for cutting through drywall, plaster, acoustical tile, wood and stucco with mesh. Made with a continuous Carbide Rim, these saws won't tear material and will leave a clean finish.

FEATURES

- Continuous Rim for clean cuts
- O Carbide Grit Edge for abrasive materials
- O Solid, Welded Construction provides accurately-sized holes

RECESSED LIGHT HOLE SAWS - CONTINUOUS GRIT

Size	Description	Part No.
3-5/8"	3-1/8" Recessed Light Hole Saw	49-56-0296
4"	4-3/8" Recessed Light Hole Saw	49-56-0300
5-3/8"	5-3/8" Recessed Light Hole Saw	49-56-0303

Size	Description	Part No.
6"	6-3/8" Recessed Light Hole Saw	49-56-0305
6"	6-5/8" Recessed Light Hole Saw	49-56-0310
6"	6-7/8" Recessed Light Hole Saw	49-56-0315

SHOCKWAVE™ IMPACT HOLE SAWS

OVERVIEW

Designed with a robust 1/4" quick change hex shank, MILWAUKEE® SHOCKWAVE™ Impact Hole Saws give professionals a hole-making solution to use with impact drivers. Utilizing a thin wall 8 TPI design, Impact Hole Saws deliver a burr-free cut up to 40% faster than standard bi-metal hole saws. The included ejection spring removes the frustration of manually removing slugs by automatically ejecting the material. A stop shoulder design prevents over-drilling into material and potentially damaging inner components of electrical and junction boxes. Choose Impact Hole Saws for use in plastics and thin-gauge metals up to 1/8" thick.

FEATURES

- 1/4" Quick Change Hex Shank for use with impact drivers
- O Thin Wall 8 TPI Design for 40% faster cuts than standard bi-metal hole saws
- Stop Shoulder Design prevents over-drilling and damaging components

SHOCKWAVE™ IMPACT HOLE SAWS SHO

OHOOKHATE IIII AOT HOEE OAHO	
Size	Part No.
3/4"	49-56-9805
7/8"	49-56-9810
1"	49-56-9815
1-1/8"	49-56-9820
1-1/4"	49-56-9825
1-3/8"	49-56-9830
1-1/2"	49-56-9835

|--|

Description	Includes	Part No.
3 Pc SHOCK Impact Saw Kit	(1) 1-1/8" SHOCKWAVE" Impact Hole S	aw 49-22-4800



SHOCKWAVE /