

METAL CUTTING CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness	Arbor	Part No.
5-3/8"	30	Metal and Stainless	0°	0.063"	20 mm	48-40-4070
5-3/8"	30	Metal and Stainless	0°	0.063"	5/8"	48-40-4205
5-7/8"	34	Metal	2°	0.063"	20 mm	48-40-4215
6-1/2"	48	Metal	2°	0.063"	5/8"	48-40-4220
6-7/8"	36	Metal	2°	0.063"	20 mm	48-40-4225
7"	40	Metal	2°	0.071"	20 mm	48-40-4230
7-1/4"	48	Metal	2°	0.071"	5/8"	48-40-4235
7-1/4"	48	Metal	2°	0.071"	20 mm	48-40-4237
7-1/4"	70	Thin Metal	-5°	0.071"	5/8"	48-40-4240
8"	42	Metal and Stainless	0°	0.073"	5/8"	48-40-4515
8"	50	Thin Metal and Stainless	0°	0.073"	5/8"	48-40-4520
9"	48	Metal	0°	0.071"	1"	48-40-4255
10"	50	Metal	0°	0.079"	5/8"	48-40-4260
12"	60	Metal	0°	0.087"	1"	48-40-4265
14"	72	Metal and Stainless	0°	0.087"	1"	48-40-4505
14"	90	Thin Metal	10°	0.087"	1"	48-40-4510
5-3/8"	50	Aluminum	-5°	0.063"	20 mm	48-40-4075
5-7/8"	50	Aluminum	-5°	0.071"	20 mm	48-40-4315
6-1/2"	54	Aluminum	-5°	0.071"	5/8"	48-40-4320
7"	54	Aluminum	-5°	0.079"	20 mm	48-40-4330
7-1/4"	56	Aluminum	-6°	0.079"	5/8"	48-40-4335
8"	58	Aluminum	-6°	0.094"	5/8"	48-40-4345
9"	72	Aluminum	-6°	0.094"	1"	48-40-4355
10"	72	Aluminum	-6°	0.110"	5/8"	48-40-4360
12"	80	Aluminum	-6°	0.118"	1"	48-40-4365
14"	80	Aluminum	-6°	0.126"	1"	48-40-4370

FIBER CEMENT CUTTING CIRCULAR SAW BLADES
OVERVIEW

MILWAUKEE® Fiber Cement Circular Saw Blades provide up to 75X longer life, increased accuracy and cooler cuts in fiber cement applications. The blades are designed utilizing Polycrystalline Diamond Teeth to extend cutting life in fiber cement material. The blades feature Laser Cut Vibration Slots to reduce wobble and warping. With an Anti-Friction Coating, the blades resist corrosion and gumming. MILWAUKEE's Circular Saw Blades are optimized for cordless and corded performance.


FEATURES

- Polycrystalline Diamond Teeth: Extend cutting life in fiber cement up to 75X longer
- Anti-Friction Coating: Provides cooler cuts
- Laser Cut Vibration Slots: Increase blade accuracy and prevent wobble and warping

CARBIDE TEETH
FIBER CEMENT CUTTING CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (mm)	Tooth Grind	Part No.
7-1/4"	4T	Fiber Cement	10°	0.071	ATB	48-40-7000
10"	6T	Fiber Cement	10°	0.079	ATB	48-40-7010
12"	8T	Fiber Cement	10°	0.087	ATB	48-40-7020

CIRCULAR SAW ACCESSORIES
CIRCULAR SAW ACCESSORIES

Description	Part No.
Dust Collection Kit	49-22-8105
Extension Kit	49-22-8108
Hold Down Bar Kit	49-22-8100
Mid-Way Fence Kit	49-22-8110

Description	Part No.
Quick Stop Gauging Kit	49-22-8102
Riser Support	48-08-0360
Tool Stand	48-08-0350

Description	Part No.
Wedge Clamps	48-08-0380
Wheel Kit	49-22-8106
Work Center	48-08-0450