

SPLINE ONE-PIECE CORE BITS

OVERVIEW

CONCRETE DRILLING

MILWAUKEE's One-Piece Carbide Tipped Core Bits are ideal for drilling large holes where the depth is relatively shallow. The core bit cuts a kerf only. The inside core must be removed by the operator before deeper drilling can be accomplished. Centering Bit 48-20-5495 is included. Use Drift Key 48-20-5497 (not included) to remove centering bit from the one-piece core bit. The one-piece core bits are available in SDS Max or Spline shanks. They come in a variety of diameters ranging from 1-1/2" to 6" with overall lengths of 11-3/8" or 22" and a drilling depth of 3". The asymmetric tooth pitch with alternating tooth geometries creates faster material pulverization. The one-piece design maximizes energy transfer and the thick wall core body is durable even in large hammers. The fluted core exterior minimizes friction loss and removes debris faster.



FEATURES

- Asymmetrical and Alternating Teeth for faster material pulverization
- O Thick Wall Core Body for durability even in large hammers
- O Includes Centering Bit to reduce bit walking and create exact spot drilling

SPLINE ONE-PIECE CORE BITS

Diameter	Length	Part No.
1-1/2"	11-3/8"	48-20-5450
1-1/2"	22"	48-20-5452
1-3/4"	11-3/8"	48-20-5454
1-3/4"	22"	48-20-5456
2"	11-3/8"	48-20-5458
2"	22"	48-20-5460

Diameter	Length	Part No.
2-5/8"	11-3/8"	48-20-5462
2-5/8"	22"	48-20-5464
3-1/8"	11-3/8"	48-20-5470
3-1/8"	22"	48-20-5472
3-9/16"	11-3/8"	48-20-5478
3-9/16"	22"	48-20-5480

Diameter	Length	Part No.
4"	11-3/8"	48-20-5482
4"	22"	48-20-5484
5"	11-3/8"	48-20-5486
5"	22"	48-20-5488
6"	22"	48-20-5490

SPLINE ONE-PIECE CORE BITS ACCESSORIES

Description	Part No.
One-Piece Core Bit Centering Bit	48-20-5495
Drift Key for One-Piece Core Bits	48-20-5497

SPLINE OR ROUND/HEX DEMOLITION STEEL



SPLINE OR ROUND/HEX DEMOLITION STEEL

Style	Size	1 Pack	Bulk
Bull Point	12"	48-62-2000	48-62-2100 (25 pk)
Bull Point	18"	48-62-2010	48-62-2110 (25 pk)
Bushing Tool	1-3/4" x 9-1/2"	48-62-2070	48-62-2170 (15 pk)
Clay Spade	4-1/2" x 16-3/4"	48-62-2095	-
Flat Chisel	1" x 12"	48-62-2020	48-62-2120 (25 pk)
Flat Chisel	1" x 18"	48-62-2030	48-62-2130 (25 pk)
Ground Rod Driver	10"L - 5/8" & 3/4" Rod Diameter	48-62-2046	-
Scaling Chisel	1-1/2" x 12"	48-62-2040	-
Scaling Chisel	2" x 12"	48-62-2050	48-62-2150 (25 pk)
Scaling Chisel	3" x 12"	48-62-2055	48-62-2155 (25 pk)
Scaling Chisel	4-1/2" x 14"	48-62-2057	-
Scraping Chisel	2" x 12"	48-62-2065	-
Seam Tool	1" x 12"	48-62-2080	-
Slotting Chisel	1-1/4" x 12"	48-62-2060	-
Tamper Plate	5" x 5"	48-62-3060	-
Tamper Shank	12"	48-62-2097	-

HEX

3/4" HEX DEMOLITION STEEL



3/4" HEX DEMOLITION STEEL

Style	Size	Part No.	
Asphalt Cutter	5" x 16-1/2"	48-62-3090	
Bull Point	12"	48-62-3000	
Bull Point	18"	48-62-3005	
Bushing Tool	1-3/4" x 9-1/2"	48-62-3085	
Clay Spade	4-1/2" x 16-3/4"	48-62-3040	
Flat Chisel	1" x 12"	48-62-3010	
Flat Chisel	1" x 18"	48-62-3015	

_			
	Style	Size	Part No.
	Ground Rod Driver	9-3/4"L - 5-8" & 3/4" Rod Diameter	48-62-3070
	Scaling Chisel	1-1/2" x 12"	48-62-3020
	Scaling Chisel	2" x 12"	48-62-3035
	Scaling Chisel	3" x 12"	48-62-3030
	Scraping Chisel	2" x 12"	48-62-3025
	Tamper Shank	12"	48-62-3065
_			