

CARBIDE HOLE CUTTER ACCESSORIES
CARBIDE HOLE CUTTER ACCESSORIES

Description	Part No.
3/8" Shank Quick Change Adapter for Sheet Metal & Steel Plate Cutters	49-57-0035
Centering Pin Arbor with Detachable Drill Cap	49-57-0037
Compact Electromagnetic Drill to 1/2" Chuck Adapter	48-66-2125
Drill Cap for 49-57-0037 Arbor	42-52-1015

Description	Part No.
Ejection Spring for 49-57-0035	40-50-8780
HAWG WASH™ Hand Pump	44-46-0090
HAWG WASH™ Hand Pump Oil Hose	43-75-0010
Pilot Bit	49-57-0038

CIRCULAR SAW BLADES
WOOD CUTTING CIRCULAR SAW BLADES
OVERVIEW

MILWAUKEE® Circular Saw Blades provide longer life, increased accuracy and cooler cuts in wood cutting applications. The blades are designed utilizing application-specific Cobalt Infused Tungsten Carbide to extend cutting life and maintain tip sharpness. The blades feature Laser Cut Vibration Slots to reduce wobble and warping. With an Anti-Friction Coating, the blades resist corrosion and gumming. MILWAUKEE's Circular Saw Blades are optimized for cordless and corded performance.


CARBIDE TEETH
FEATURES

- Cobalt Infused Tungsten Carbide: Extends cutting life and maintains tip sharpness
- Anti-Friction Coating: Provides cooler cuts
- Laser Cut Vibration Slots: Increase blade accuracy and prevent wobble and warping

WOOD CUTTING CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (mm)	Tooth Grind	Part No.	10 Pack (Bulk)
5-3/8"	16	Framing	15°	0.063	15° ATB	48-40-0522	-
5-3/8"	36	Finish	15°	0.063	15° ATB	48-40-0524	-
5-1/2"	18	Framing	18°	0.063	15° ATB	48-40-0520	-
6-1/2"	24	Framing	18°	0.063	15° ATB	48-40-0620	48-41-0620
6-1/2"	40	Finish	15°	0.063	15° ATB	48-40-0622	-
7-1/4"	24	Framing	20°	0.063	12° ATB	-	48-41-0710
7-1/4"	24	Framing	18°	0.063	15° ATB	48-40-0720	48-41-0720
7-1/4"	24	Framing	20°	0.063	12° ATB	-	48-41-0713

WOOD CUTTING CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (mm)	Tooth Grind	Part No.	10 Pack (Bulk)
7-1/4"	24	Framing	18°	0.063	15° ATB	-	48-41-0723
7-1/4"	40	Finish	15°	0.063	15° ATB	48-40-0726	48-41-0726
7-1/4"	60	Finish	15°	0.063	30° ATB	48-40-0730	48-41-0730
8-1/4"	24	Framing	18°	0.083	15° ATB	48-40-0820	-
8-1/4"	40	Finish	15°	0.083	15° ATB	48-40-0822	-
8-1/4"	60	Finish	12°	0.094	15° ATB	48-40-0826	-
8-1/2"	40	General Purpose	15°	0.094	10° ATB	48-40-0824	-
10"	24	Ripping	22°	0.094	15° ATB	48-40-1020	-
10"	40	General Purpose	15°	0.094	10° ATB	48-40-1024	-
10"	50	Combination	12°	0.094	15° FTG + ATB	48-40-1026	-
10"	60	Finish	12°	0.094	25° ATB	48-40-1028	-
10"	80	Finish	12°	0.094	25° ATB	48-40-1032	-
10"	40 & 60	General Purpose/Finish	15° & 12°	0.094 & 0.094	10° & 25° ATB	48-40-1036	-
10-1/4"	28	Framing	18°	0.102	15° ATB	48-40-1038	-
10-1/4"	40	Finish	12°	0.102	15° ATB	48-40-1040	-
12"	44	General Purpose	15°	0.118	10° ATB	48-40-1220	-
12"	60	Combination	12°	0.118	15° ATB	48-40-1222	-
12"	80	Finish	12°	0.118	25° ATB	48-40-1224	-
12"	100	Finish	12°	0.118	30° ATB	48-40-1228	-
12"	44 & 80	General Purpose/Finish	15° & 12°	0.118 & 0.118	10° & 25° ATB	48-40-1232	-

NEW
METAL CUTTING CIRCULAR SAW BLADES
OVERVIEW

MILWAUKEE® Metal Cutting Circular Saw Blades were specifically designed to exceed contractors expectations for blade life, cut quality and speed in the most demanding metal cutting applications – without a lubricant. A hand-tensioned, hardened alloy steel body minimizes vibration to extend blade life and delivers the highest quality cuts available. Carbide teeth shear through metal leaving burr-free, cool-to-touch cuts.

FEATURES

- Dry: No lubricant required, saving time and money with less mess
- Cool: No extreme heat buildup preserves blade life and allows handling the work piece immediately
- Clean: No burrs eliminates secondary operations, saving time and money


CARBIDE TEETH