

**FEBF721**

Eye/Face Wash, Wall Mounted, Barrier-Free



**Application:** Barrier-free WideArea™ eye/face wash for wall mounting.

**ADA Compliance:** Bowl is lowered and extended to permit access by wheelchair user. Profile of unit is “flattened” to comply with maximum height and knee clearance requirements. When installed at recommended mounting height, unit complies with ADA requirements for accessibility by handicapped persons.

**Mounting:** Wall-mounted bowl unit has welded stainless steel wraparound skirt to conceal valve, drain and piping.

**Spray Head Assembly:** Four GS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

**Valve:** 1/2" IPS brass stay-open ball valve. Valve is US-made with chrome plated brass ball and PTFE seals.

**Bowl:** 11-1/2" (292mm) diameter stainless steel bowl.

**Supply:** 1/2" NPT female inlet.

**Waste:** 1-1/2" OD chrome plated brass tailpiece.

**Sign:** Furnished with universal identification sign.

**Quality Assurance:** Unit is fully assembled and water tested prior to shipment. Unit is third-party certified to comply with ANSI Z358.1-2014.

**FEBF724**

Eye/Face Wash, Wall Mounted, Barrier-Free



**Application:** Barrier-free WideArea™ eye/face wash for wall mounting.

**ADA Compliance:** Bowl is lowered and extended to permit access by wheelchair user. Profile of unit is “flattened” to comply with maximum height and knee clearance requirements. When installed at recommended mounting height, unit complies with ADA requirements for accessibility by handicapped persons.

**Mounting:** Welded stainless steel bracket for wall mounting.

**Spray Head Assembly:** Four GS-Plus™ spray heads. Each head has a “flip top” dust cover, internal flow control and filter to remove impurities from the water flow.

**Valve:** 1/2" IPS chrome plated brass stay-open ball valve. Valve is US-made with chrome plated brass ball and PTFE seals.

**Bowl:** 11-1/2" (292mm) diameter stainless steel.

**Supply:** 1/2" NPT female inlet.

**Waste:** 1-1/2" OD chrome plated brass tailpiece.

**Sign:** Furnished with universal identification sign.

**Quality Assurance:** Unit is fully assembled and water tested prior to shipment. Unit is third-party certified to comply with ANSI Z358.1-2014.

**Optional Features:**

- Stainless steel dust cover for each spray head (add suffix “DC”)
- Chrome plated brass tailpiece and trap with 1-1/2" IPS waste connection (add suffix “T”)

**Accessories:**

- AP3600 thermostatic mixing valve blends hot and cold water to deliver tepid water as provided by ANSI Z358.1-2014 (add suffix “TMV”). Refer to “Tempering Valves” section for complete technical information.