# SL1000 Portable Parallel Analyzer (PPA)



#### **Applications**

- Chloramination
- Drinking Water
- Clean Water
- Boiler Water
- Cooling Water

## **Chloramination Testing Can be Done 75% Faster**

The new Hach<sup>®</sup> SL1000 Portable Parallel Analyzer<sup>®</sup> (PPA) performs the same tests with less than half the manual steps. Get highly accurate results with less opportunity for errors in a fraction of the time. Up to six parameters tested simultaneously.

#### Perform multiple tests faster

Complete more tests on site, get the results you need faster, allowing you to visit more sites in each shift. Perform up to four colorimetric and two probe based measurements in parallel 75% faster than with other methods.

#### **Less Variability**

Automation and internal temperature control make the entire process consistent and repeatable, while applying the same processes as current Hach methods. Avoid manual steps that can introduce variability, even when performed by experienced testers.

#### **Less Hassle**

A single instrument combines colorimetric and probe testing in a field kit that requires fewer bulky accessories. All chemicals and processes are entirely contained inside the Chemkey<sup>®</sup>. There are no powder pillows or glass vials to handle.





#### **Technical Data\***

Battery Requirements Rechargeable Lithium-Ion battery pack

>200 Chemkey tests per full battery charge

CertificationsCE CompliantDetectorSilicon photodiode

**Dimensions (H x W x D)** 258.3 mm x 130.8 mm x 58.9 mm

Interfaces Mini USB

**Measurement Modes** Transmittance (%), Absorbance (abs) and Concentration (Conc) **Operating Temperature** 5 - 50 °C / maximum 85% relative humidity (non-condensing)

Range

Protection Class

Storage Conditions -20 - 60 °C / maximum 85% relative humidity (non-condensing)

**Enclosure Rating** IP64

**Weight** 2.65 lbs. (1.2 kg)

Warranty 1 year

\*Subject to change without notice.

### **Chemkey Reagents\***

Chemkey tests are available for the following parameters and ranges:

| Parameter                               | Range   | Quantity | Prod. No. |
|---|---|----------|-----------|
| Free Chlorine                           | 0.04 - 4.00 mg/L Cl <sub>2</sub>  | pk/25    | 9429000   |
| Free Chlorine                           | 0.04 - 4.00 mg/L Cl <sub>2</sub>  | pk/300   | 8499300   |
| Total Chlorine                          | 0.04 - 10 mg/L Cl <sub>2</sub>  | pk/25    | 9429100   |
| Total Chlorine                          | 0.04 - 10 mg/L Cl <sub>2</sub>  | pk/300   | 8499400   |
| Monochloramine                          | 0.04 - 4.00 mg/L Cl <sub>2</sub>  | pk/25    | 9429400   |
| Free Ammonia<br>Monochloramine          | Free Ammonia: 0.05 - 0.50 mg/L NH <sub>3</sub> -N<br>Monochloramine: 0.04 - 4.00 mg/L Cl <sub>2</sub>   | pk/50    | 9429600   |
| Nitrite                                 | 0.005 - 0.600 mg/L NO <sub>2</sub> -N   | pk/25    | 9429300   |
| Total Ammonia                           | 0.05 - 1.50 mg/L NH <sub>3</sub> -N   | pk/25    | 9425200   |
| Ammonia, Free & Total<br>Monochloramine | Free Ammonia: 0.05 - 0.50 mg/L NH <sub>3</sub> -N<br>Total Ammonia: 0.05 - 1.50 mg/L NH <sub>3</sub> -N<br>Monochloramine: 0.04 - 4.00 mg/L Cl <sub>2</sub> | pk/50    | 8791900   |
| Copper                                  | 0.06 - 5.00 mg/L Cu   | pk/25    | 9429200   |
| Dissolved Iron                          | 0.05 - 3.00 mg/L Fe   | pk/25    | 8636000   |
| Alkalinity                              | 200 - 700 mg/L CaCO <sub>3</sub>  | pk/25    | 8636100   |
| Alkalinity                              | 20 - 200 mg/L CaCO <sub>3</sub>   | pk/25    | 8636200   |
| Hardness                                | 90 - 750 mg/L CaCO <sub>3</sub>   | pk/25    | 8636300   |
| Hardness                                | 3 - 100 mg/L CaCO <sub>3</sub>  | pk/25    | 8636400   |
| Orthophosphate                          | 2.0 - 30.0 mg/L PO <sub>4</sub>   | pk/25    | 8636500   |
| Orthophosphate                          | 0.20 - 4.00 mg/L PO <sub>4</sub>  | pk/25    | 8636600   |
| Peracetic Acid                          | 0.04 - 50.0 mg/L PAA  | pk/25    | 8635200   |
| рН                                      | pH 6.3 - 9.0  | pk/25    | 9759000   |

\*Subject to change without notice.



#### **Order Information**

#### **SL1000 Instrument Options**

9430000 SL1000 Portable Parallel Analyzer (PPA)

Includes: SL1000 meter, carrying case, 1 instrument sample cup, 2 probe sample cups, rechargeable battery, battery charger,

hand strap, instrument manual, and USB cable.

8499000 Full SL1000 Portable Parallel Analyzer (PPA) Kit

Full kit includes basic instrument package plus: 1 pH probe, 1 conductivity probe and 1 box each of Free Cl, Total Cl, Monochloramine, Nitrite and Free Ammonia Chemkeys.

25632200 Full SL1000 Portable Parallel Analyzer (PPA) Nitrification Kit

SL1000 meter, 1 pH probe, 1 nitrate probe, 1 box each of Free Cl,

Total CI, MonoCI, Free Ammonia and Nitrite Chemkeys,

carrying case, 1 instrument sample cup, 2 probe sample cups, rechargeable battery, battery charger, handstrap, instrument manual,

and USB cable.



9427900 Chlorine Verification Chemkey9436800 System Verification Chemkey

9374200 Car Charger for SL1000 Portable Parallel Analyzer

PHC20101 Intellical™ PHC201 Standard gel filled pH electrode, 1 m cable
 CDC40101 Intellical™ CDC401 Standard Conductivity electrode, 1 m cable
 MTC10101 Intellical™ MTC101 Standard gel filled ORP electrode, 1 m cable
 LDO10101 Intellical™ LDO101 Standard Luminescent/Optical Dissolved Oxygen

(LDO) sensor, 1 m cable

ISEN0318101Intellical™ ISENO3181 Standard Nitrate ISE electrode, 1 m cableISEF12101Intellical™ ISEF121 Standard Fluoride ISE electrode, 1 m cableISECL18101Intellical™ ISECL181 Standard Chloride ISE electrode, 1 m cable

**ISENA381AP** Intellical™ ISENA38101 Standard Sodium ISE electrode

with calibration reagents pack

ISENH4181AP Intellical™ ISENH418101 Standard Ammonia ISE electrode

with calibration reagents pack

2522905 Cotton-Tipped Applicator

1440049 Sodium Chloride Standard Solution,

491 mg/L NaCl (1000 μS/cm), 500 mL

2316949 ZoBell's Standard Solution, 500 mL





Hach World Headquarters: Loveland, Colorado USA

United States: 800-227-4224 tel 970-669-2932 fax orders@hach.com
Outside United States: 970-669-3050 tel 970-461-3939 fax int@hach.com

hach.com

Printed in U.S.A.

©Hach Company, 2020. All rights reserved.

In the interest of improving and updating its equipment, Hach Company reserves the right to alter specifications to equipment at any time.

