

BioPette™ A Single- and Multi-channel Pipettors

Available in single-, 8-, and 12-channel configurations, all BioPette A Pipettors are autoclavable and feature smooth plunger movement with low pipetting forces. Volume can be set by turning either the thumb wheel or the plunger button. BioPette A pipettors have been designed to maintain their calibration, even after repeated use and autoclaving. A calibration key is included with each pipettor for easy in-house calibration.

BioPette A multi-channel pipettors feature individually spring-loaded piston assemblies for positive tip sealing and a curved ejector bar requiring minimal ejection force. The multi-channel manifold rotates 360° for ejecting and pipetting in any position.

Features


- Factory calibrated to strict ISO 8655 standards
- Calibration key included with each pipettor for easy in-house calibration
- Fully autoclavable and UV-resistant
- Designed for universal fit with all common brands of pipet tips
- Adjustable tip ejector in all single-channel models
- 3-year warranty



Ordering Information

Cat. No.	Volume Range (μL)	Channels	Accuracy (%)	Precision (%)	Non-filtered Tip (μL)
P3960-2A	0.1-2	1	±40.0 to ±1.5	≤12.0 to ≤0.7	10
P3960-10A	0.5-10	1	±4.0 to ±0.5	≤2.8 to ≤0.4	10
P3960-20A	2-20	1	±3.0 to ±0.8	≤1.5 to ≤0.3	200
P3960-100A	10-100	1	±1.6 to ±0.8	≤0.8 to ≤0.2	200
P3660-200A	20-200	1	±1.2 to ±0.6	≤0.6 to ≤0.2	200
P3960-1000A	100-1,000	1	±1.6 to ±0.6	≤0.4 to ≤0.15	1,000
P3960-5000A	1,000-5,000	1	±0.6 to ±0.5	≤0.25 to ≤0.15	5,000
P3960-10000A	1,000-10,000	1	±2.5 to ±0.5	≤0.6 to ≤0.2	10,000
P4608-10A	1-10	8	±8.0 to ±2.0	≤6.0 to ≤1.2	10
P4608-50A	5-50	8	±4.0 to ±1.6	≤2.5 to ≤0.6	200
P4608-200A	20-200	8	±3.0 to ±1.0	≤1.5 to ≤0.6	200
P4608-300A	50-300	8	±1.6 to ±1.0	≤1.5 to ≤0.6	300
P4612-10A	1-10	12	±8.0 to ±2.0	≤6.0 to ≤1.2	10
P4612-50A	5-50	12	±4.0 to ±1.6	≤2.5 to ≤0.6	200
P4612-200A	20-200	12	±3.0 to ±1.0	≤1.5 to ≤0.6	200
P4612-300A	50-300	12	±1.6 to ±1.0	≤1.5 to ≤0.6	300

Cat. No.	Description
P3960-SK4	Labnet BioPette A Starter Kit Includes 4 single-channel pipettors with calibration keys and shelf clips: 0.5-10 μL (Cat. No. P3960-10A), 2-20 μL (Cat. No. P3960-20A), 20-200 μL (Cat. No. P3960-200A), 100-1,000 μL (Cat. No. P3960-1000A); universal carousel stand for six single-channel pipettors (Cat. No. P3985-P); 3 racks of pipet tips: 10 μL (Cat. No. P1000-10-R), 200 μL (Cat. No. P1000-200-R), and 1,000 μL (Cat. No. P1000-1000-R).



QC certificate delivered with each product