# **HDR115**

### **Direct Fired Air Heaters**







#### **HDR115 Direct Fired Radiant Heater**

Infrared radiant heaters direct heat exactly where you need it without relying on warming the surrounding air, unlike convective heat, making it unaffected by the wind or weather. Perfect for heating open work spaces, personnel, equipment, concrete form work, or job site structures, radiant heaters emit clean, dry heat from the face of the heater, while venting combustion gases upwards and away from the surfaces or personnel you are heating.

- Best in class 115,000 BTU/hr to maximize your heat output with an operating range of -25  $\circ$ C to 45  $\circ$ C.
- An active air cooling system keeps the rear of the machine significantly cooler than competitive models without the need for refractory panels.
- Pneumatic tires and single point lift bail for easy transport, along with rugged rotomolded plastic fuel tank with 13.4 hour run time, make these heaters jobsite and rental friendly.
- Front panel made from 300 series stainless steel for extreme performance and longevity.
- Heaters are CSA approved.

## HDR115 Technical specifications

#### **Dimensions**

L x W x H Overall	35.24 x 20.94 x 31.81 in
L x W x H Shipping	29.1 x 22.4 x 27.7 in
Operating weight without fuel	92.5 lb
Shipping weight	105.8 lb
Operating data	
Heating power Gross Heat Input	115,000 BTU/h
Fuel type	Diesel #2
Fuel consumption	0.758 US gal/h
Tank capacity	11.35 US gal
Runtime	13.23 h
Voltage	120 V
Frequency	60 Hz
Current	2.15 A

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2020 Wacker Neuson SE.