

ESBF670

Recessed Emergency Shower, Exposed Shower Head



Application: Recessed emergency shower with ceiling mounted exposed shower head.

ADA Compliance: When installed at recommended mounting heights, unit complies with ADA requirements for accessibility by handicapped persons.

Shower Head: 10" (254mm) diameter stainless steel. Furnished with vertical supply pipe and ceiling escutcheon.

Valve: 1" IPS brass stay-open ball valve with stainless steel "panic bar." Pulling bar down activates shower; shower remains in operation until bar is returned to original closed position. Furnished with stainless steel access panel and 1" IPS unions for valve.

Pipe and Fittings: Exposed pipe and escutcheon are stainless steel.

Supply: 1" NPT female inlet.

Sign: Furnished with universal identification sign.

Quality Assurance: Unit is assembled and water tested prior to shipment. Unit is third-party certified to comply with ANSI Z358.1-2014.

U.S. Patent 5,768,721

See SSBF672 for description of available options and accessories.

ESBF671

Recessed Emergency Shower, Recess Mounted Shower Head



Application: Recessed emergency shower with ceiling mounted recessed shower head.

ADA Compliance: When installed at recommended mounting heights, unit complies with ADA requirements for accessibility by handicapped persons.

Shower Head: 10" (254mm) diameter stainless steel with flanged rim for recessed mounting in ceiling.

Valve: 1" IPS brass stay-open ball valve with stainless steel "panic bar." Pulling bar down activates shower; shower remains in operation until bar is returned to original closed position. Furnished with stainless steel access panel and 1" IPS unions for valve.

Supply: 1" NPT female inlet.

Sign: Furnished with universal identification sign.

Quality Assurance: Unit is assembled and water tested prior to shipment. Unit is third-party certified to comply with ANSI Z358.1-2014.

Note: ANSI Z358.1-2014 provides that shower heads be installed no more than 96" above the finished floor. This unit should therefore not be installed in ceilings or soffits over 8 feet. For higher ceiling heights, we recommend the ESBF670 or ESBF672 units.

U.S. Patent 5,768,721

See SSBF672 for description of available options and accessories.