Laboratory Mixing Faucets



L412VB

Mixing Faucet, Deck Mounted, Vacuum Breaker



Application: Deck mounted mixing faucet with vacuum breaker for hot and cold water

Body: Forged brass.

Valve Units: WaterSaver self-contained compression valve units with replaceable stainless steel seats.

Handles: Forged brass four-arm handles with color-coded index discs.

Gooseneck: 6" swing gooseneck.

Vacuum Breaker: Integral vacuum breaker to prevent backflow. Vacuum breaker has replaceable seat and ultra-light float cup to resist spilling at low flow.

Inlet: 1-3/16" male shank with (2) 3/8" OD flexible copper tubes. Furnished complete with locknut and washer.

Outlet: 3/8" NPS female outlet with removable anti-splash serration hose end.

Quality Assurance: Faucet is fully assembled and factory tested prior to shipment.

Additional Models

L411VB: Same as above except with rigid gooseneck.

L414VB: Same as above except with convertible rigid/swing gooseneck.

Note: If vacuum breaker is not required, delete suffix "VB".

L412VB-BH

Mixing Faucet, Deck Mounted, Vacuum Breaker and Blade Handles





Application: Deck mounted mixing faucet with vacuum breaker and wrist blade handles for hot and cold water.

Body: Forged brass.

Valve Units: WaterSaver self-contained compression valve units with replaceable stainless steel seats.

Handles: Forged brass wrist blade handles with color-coded index discs.

Gooseneck: 6" swing gooseneck.

Vacuum Breaker: Integral vacuum breaker to prevent backflow. Vacuum breaker has replaceable seat and ultra-light float cup to resist spilling at low flow.

Inlet: 1-3/16" male shank with (2) 3/8" OD flexible copper tubes. Furnished complete with locknut and washer.

Outlet: 3/8" NPS female outlet with removable anti-splash serration hose end.

Quality Assurance: Faucet is fully assembled and factory tested prior to shipment.

Additional Models

L411VB-BH: Same as above except with rigid gooseneck.

L414VB-BH: Same as above except with convertible rigid/swing gooseneck.

Note: If vacuum breaker is not required, delete suffix "VB".

L410

Mixing Faucet, Deck Mounted, Swing Spout



Application: Deck mounted faucet for hot and cold water.

Body: Forged brass.

Valve Units: WaterSaver self-contained compression valve units with replaceable stainless steel seats.

Handles: Forged brass four-arm handles with color-coded index discs.

Spout: 9" swing spout.

Inlet: 1-3/16" male shank with (2) 3/8" OD flexible copper tubes. Furnished complete with locknut and washer.

Outlet: 3/8" NPS female outlet with removable aerator.

Quality Assurance: Faucet is fully assembled and factory tested prior to shipment.

Additional Model

L410VB: Same as above except with vacuum breaker.

Options for Single and Mixing Faucets

Valve Units: Compression valve units with adjustable volume controls (add prefix "LA") or ceramic disc valve units (add prefix "LC"). **Gooseneck:** 8" spread gooseneck in place of 6" (add suffix "8"). For other gooseneck spreads and heights, please refer to page 56. **Outlet:** BO055 aerator in place of serrated hose end (add suffix "55").

WaterSaver Faucet Co. wsflab.com 15