

ARFU26

Consolidation of in-situ Concrete



**WACKER
NEUSON**
all it takes!



Quality exposed concrete surface to satisfy high expectations.

Wacker Neuson external vibrators have been used for concrete consolidation for many years. This ARFU26 external vibrator was designed specifically for cast-in-place formwork as well as light precast concrete applications. Its low weight, compact size, and ability to

keep a constant speed under load make it the preferred external vibrator for concrete consolidation worldwide.

- Extremely versatile thanks to its integrated frequency inverter
- Continuous duty thanks to its powerful, well designed electric motor
- Specially designed for cast-in-place jobsite applications or light precast
- Fast assembly thanks to easy to use fastening clamps
- Brushless asynchronous motor alleviates the need to change brushes

ARFU26 Technical specifications

	ARFU26/6/230	ARFU26/6/115 UK	ARFU26/6/120 US
Vibrations rpm	6,000	6,000	6,000
Centrifugal force max. lbf	780.1	780.1	780
Voltage V	220-240	110-130	110-130
Rated current A	6	12	12
Weight lb	24.7	24.69	24.7
L x W x H in	9.1 x 8.9 x 4.1	9.1 x 8.9 x 4.1	9.1 x 8.9 x 4.1
Fastening	90 x 125	90 x 125	90 x 125

* plus 2 meters supply cable

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2020 Wacker Neuson SE.