

BenchPro™ BP-S

Shipping Bench Scale



Standard Features

- Simple operation, easy to set up
- Large six-digit backlight LCD display with 1 in (29 mm) characters protected by heavy duty tempered glass
- Powered USB HID point of sale interface – kg model only
- Nine-pin RS-232 interface for use with SMA and NCI protocols
- Four AA alkaline battery operation for portability
- Gravitational compensation allows for adjustment of factory calibration to meet your local gravity setting, non-approved

APPROVALS



Measurement
Canada
Approved



Specifications

Dynamic Response:

Response time for stable weight:
0 - 1,000d, 1,000 ms, maximum mean average
1,000d +, 1,500 ms, maximum mean average

Internal Resolution:

500,000 internal count minimum

Overload Protection:

Corner & center overload protection

Power:

In-line Power Supply (included)

Input: 100-240 VAC, +10% -15%, 3-wire w/ground
Standard terminated with USA 3-prong plug

Output: 12V at .1 Amps DC minimum

Frequency: 50/60 Hz +/-3 Hz, standard

Approvals: UL, CE, EN, CUL

Battery Power (BP-S 12 x 14 scale only):

Battery Type: Four AA alkaline batteries, 6 V, with low battery indication at 4.3 volts (not included)

Battery Life: 50-250 hrs depending on backlight and auto-shutdown settings

USB HID:

USB 2.0 full speed; Vendor ID: 1C19;
Product ID: 0002

Construction:

Powder coat painted mild steel base plate and load bridge with stainless steel weight platter
BP-S 12 x 14 scale- Die-cast aluminum load bridge and base housing with stainless steel weight platter

Display:

Minimum key press life of 500,000 cycles,

ABS plastic housing

6 annunciators to indicate Zero, Gross/Brutto, Net,

W1/W2/W3 multi-range

4 buttons: Units, Tare, On/Off, F1

RS-232 Cable (included):

10 ft DB 9-pin male to female, straight pass through and null modem

USB Cable (included):

46 in (1168.4 mm) A/B type USB cable

Approvals:

NTEP COC # 17-002

Canada Weights and Measures: AM - 6050

CE Marked

Warranty:

Two-year limited warranty



BP-S 12 x 14 in

Part Number/Price

| Part # | Platform Capacity | Dimensions | Est. Weight | Price |
|----------|------------------------------|------------|-------------|------------|
| 174879 * | 150 x 0.05 lb (75 x 0.02 kg) | 12 x 14 in | 17 lb | \$565.00 |
| 182993 | 150 x 0.05 lb (75 x 0.02 kg) | 12 x 16 in | 31 lb | \$745.00 |
| 182391 | 100 x 0.02 lb (50 x 0.01 kg) | 18 x 18 in | 63 lb | \$1,095.00 |
| 182378 | 150 x 0.05 lb (75 x 0.02 kg) | 18 x 18 in | 63 lb | \$1,095.00 |
| 182382 | 300 x 0.1 lb (150 x 0.05 kg) | 18 x 18 in | 63 lb | \$1,095.00 |
| 182395 | 300 x 0.1 lb (150 x 0.05 kg) | 20 x 20 in | 76 lb | \$1,295.00 |
| 182399 | 300 x 0.1 lb (150 x 0.05 kg) | 24 x 24 in | 131 lb | \$1,495.00 |

* Battery or DC power

Options/Accessories

| Part # | Description | Est. Weight | Price |
|--------|--|-------------|----------|
| 174783 | Column bracket and post (12 x 14 scale only) | 2 lb | \$45.00 |
| 180901 | Second Customer display, BenchPro BP-S no keyboard with 68 in cable | 4 lb | \$65.00 |
| 174784 | Second Remote operator display, BenchPro BP-S with 68 in cable | 4 lb | \$80.00 |
| 183103 | 16 in (H) tabletop display post for use with second display, customer or remote operator | 4 lb | \$195.00 |
| 178501 | USB-RS-232 serial adapter | 1 lb | \$45.00 |

Dimensions - Inches

| | A | B | C | D |
|---------|----|----|-------|------|
| 12 x 14 | 12 | 14 | 14.5 | 2.70 |
| 12 x 16 | 12 | 16 | 15.30 | 4.32 |
| 18 x 18 | 18 | 18 | 21.10 | 4.30 |
| 20 x 20 | 20 | 20 | 23.10 | 4.30 |
| 24 x 24 | 24 | 24 | 27.10 | 4.30 |

