


# UltraStudio HD Mini



UltraStudio HD Mini features professional broadcast quality connections that include 3G-SDI, analog YUV and composite NTSC/PAL video inputs, along with a reference input. There are also two 1/4" audio connections for analog audio input that work with balanced and HiFi sources. In addition, UltraStudio HD Mini can remote control professional broadcast decks using the built in RS-422 connection. For output, you get dual link 3G-SDI with fill and key, and an HDMI connection for monitoring video with a big screen television!

**\$545**

## Connections

### SDI Video Inputs

1 x 3Gb/s SD/HD switchable.

### SDI Video Outputs

2 x 3Gb/s SD/HD switchable, supports fill and key.

### SDI Rates

270Mb, 1.5G, 3G

### Optical SDI

None

### HDMI Video Inputs

None

### HDMI Video Outputs

1 x HDMI 1.4b type A connector.

### Analog Video Inputs

Y, B-Y, R-Y/NTSC/PAL.

### Analog Video Outputs

None

### Analog Audio Inputs

2 x 1/4 inch jack connectors for balanced and unbalanced analog audio.

### Analog Audio Outputs

None, embedded audio only.

### SDI Audio Inputs

16 Channels embedded in SD and HD.

### SDI Audio Outputs

16 Channels embedded in SD and HD.

### HDMI Audio Outputs

2 Channels embedded in SD and HD.

### Timecode Connection


None. RP-188 only.

### Reference Input

Tri-Sync or Black Burst.



Mini Switches and USB



---

## Supported Codecs

AVC-Intra, AVCHD, Canon XF MPEG2, Digital SLR, DV-NTSC, DV-PAL, DVCPRO50, DVCPROHD, DPX, HDV, XDCAM EX, XDCAM HD, XDCAM HD422, DNxHD, DNxHR, Apple ProRes 4444, Apple ProRes 422 HQ, Apple ProRes 422, Apple ProRes LT, Apple ProRes 422 Proxy, Uncompressed 8-bit 4:2:2, Uncompressed 10-bit 4:2:2.

---

## Software

### Software Included

Media Express, Disk Speed Test, LiveKey, Blackmagic Desktop Video Utility and Blackmagic driver on Mac and Windows. Media Express, Blackmagic Desktop Video Utility and Blackmagic driver on Linux.

### Internal Software Upgrade

Firmware built into software driver. Software driver loads upgrades at system start or via updater software.

---

## Software Applications



DaVinci Resolve



Fusion



Final Cut Pro X



Adobe Premiere Pro CC



Avid Media Composer



Adobe After Effects CC



Avid Pro Tools



Steinberg Cubase



Steinberg Nuendo



Adobe Photoshop CC

### Other supported applications include:

The Foundry Nuke, Grass Valley Edius, Sony Catalyst Production Suite, Tools On Air Just: Play & Live & In, Softron MovieRecorder & MReplay, Adobe Flash Media Live Encoder, Telestream Wirecast, Livestream Producer, Resolume Arena, Magix Vegas Pro & Movie Edit Pro Premium, Corel VideoStudio Pro, CyberLink PowerDirector, Vidblaster X & Studio & Broadcast, Uniplay One & CG, CasparCG Server, Magicsoft CG, Xsplit Broadcaster, Imagine Communications Velocity & InfoCaster, DevTek Easy Media Suite, Metus Ingest, Boinx Software MimoLive, Cinegy Capture Pro, vMix Live, Renewed Vision ProPresenter, Ventuz Director, Class X Liveboard & Coral CG, Glookast Capturer, Open Broadcaster Software Studio, Nautilus NEMO3D, Burst Video Webclip2Go & [REC]Marker, Autodesk Flame, Zoom.

These are third party applications and support may vary, check with your software vendor.

---

## Video Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

### HD Video Standards

720p50, 720p59.94, 720p60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p50,  
1080p59.94, 1080p60  
1080PsF23.98, 1080PsF24,  
1080PsF25, 1080PsF29.97, 1080PsF30  
1080i50, 1080i59.94, 1080i60

### 2K Video Standards

2K DCI 23.98p, 2K DCI 24p, 2K DCI  
25p, 2K DCI 23.98PsF, 2K DCI 24PsF,  
2K DCI 25PsF

### Ultra HD Video Standards

None

### 4K Video Standards

None

### SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE  
296M, SMPTE 372M and SMPTE 425M  
A/B.

### SDI Metadata Support

RP 188/SMPTE 12M-2 and closed  
captioning.

### Audio Sampling

Television rate of 48kHz and 24 bit.

### SDI Video Sampling

4:2:2/4:4:4

### Color Space

REC 601, REC 709.

### HDMI Resolution

Pixel for pixel HD resolution input  
from connected device.

### Multiple Rate support

SDI and HDMI video connections are  
switchable between standard  
definition and high definition. SDI  
switches between 270 Mb/s, 1.5 Gb/s  
and 3 Gb/s.

---

## Hardware Frame Buffer

v210 (10 bit YUV), 2vuy (8 bit YUV), ARGB, BGRA (8 bit RGB), r210 (10 bit RGB), R12B,R12L (12 bit RGB).

---

## Color Precision

### HDMI

8-bit RGB 4:4:4 up to 1080p30, and 8,  
10-bit YUV 4:2:2 in all standards.

### SDI

8, 10, 12-bit RGB 4:4:4 up to 1080p30,  
and 8, 10-bit YUV 4:2:2 in  
all standards.

---

## Computer Capture

1 x Thunderbolt™ 3 for Mac and Windows. Powers from Thunderbolt host computer, includes Blackmagic Desktop Video SDK.

---

## Control

### Built in Control Panel

None. Supports Teranex Mini Smart  
Panel with 2.2 inch color display for  
video preview, audio meters  
and status.

### Device Control

1 x RS-422 deck control.

---

## Processing

### Colorspace Conversion

Hardware based real time.

### HD Down Conversion

Real time 10-bit hardware down conversion on SDI B output when working in HD video formats on playback. Selectable between letterbox, anamorphic 16:9 and center cut 4:3 styles.

### Real Time Effects

Final Cut Pro X internal effects. Premiere Pro CC Mercury Playback Engine effects. Avid Media Composer internal effects. DaVinci Resolve.

### Physical Installation

Requires computer with a Thunderbolt™ 3 USB-C port. Please check support pages to see the full system requirements.

---

## Operating Systems



Mac 12.0 Monterey,  
Mac 13.0 Ventura or later.



Windows 10, 64-bit.  
Windows 11.



Linux

---

## Power Requirements

Powered by Thunderbolt cable. Requires computer with a Thunderbolt™ 3 USB-C port.

---

## Physical Specifications



---

## Environmental Specifications

**Operating Temperature**

5° to 40° C (32° to 104° F)

**Storage Temperature**

-20° to 45° C (-4° to 113° F)

**Relative Humidity**

0% to 90% non-condensing

---

## What's Included

UltraStudio HD Mini

Welcome wallet with QR code for software download

DaVinci Resolve SD card

---

## Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2023, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller