

Pro Dec G40 E17

Traditional globe style
LED G40 E17 lamps for
direct replacement of 11W
incandescent versions, saving
87% in running costs.



Technical Information

Series	PG40
Base	E17
Input Voltage	120V AC, 60Hz
CCT	2400K / 2700K
Wattage	1W
Lumens	Up to 32Lm (see individual product)
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed; Suitable for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply


Ordering Information

PG40-E17-UWW	Transparent / Ultra Warm White (2400K) / 25Lm
PG40-E17-WW	Transparent / Warm White (2700K) / 32Lm

Features

- SMD LED powered by on-board driver for 120V AC use in intermediate base (E17) sockets
- Nickel base resists corrosion
- Ultra clear glass lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor/outdoor use
- Sold in boxes of 25

Available CCT



2400K 2700K

Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



Pro Dec G30 E12

Traditional globe style
LED G30 E-12 lamps for
direct replacement of 11W
incandescent versions, saving
87% in running costs.



Technical Information

Series	PG30
Base	E12
Input Voltage	120V AC, 60Hz
CCT	2700K
Wattage	0.5W
Lumens	Up to 14Lm
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed; Suitable for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply

Ordering Information

PG30-E12-WW	Transparent / Warm White (2700K) / 14Lm
--------------------	---

Features

- SMD LED powered by on-board driver for 120V AC use in candelabra base (E12) sockets
- Nickel base resists corrosion
- Available in transparent lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor/outdoor use
- Sold in boxes of 25

Available CCT



2700K

Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



Pro Dec C7

Traditional style LED C7 lamps for direct replacement of 10W incandescent versions, saving 86% in running costs.



Technical Information

Series	PC7
Base	E12
Input Voltage	120V AC, 60Hz
CCT	2700K
Wattage	1W
Lumens	Up to 25Lm
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed; Suitable for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply

Ordering Information

PC7-E12-WW	Transparent / Warm White (2700K) / 25Lm
-------------------	---

Features

- SMD LED powered by on-board driver for 120V AC use in candelabra base (E12) sockets
- Nickel base resists corrosion
- Available in transparent and opaque lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor/outdoor use
- Sold in boxes of 25

Available CCT



2700K

Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



Standard LED S14

LED S14 lamps for direct replacement of 11W incandescent versions, saving 87% in running costs. For use with commercial grade light string (sold separately).



Technical Information

Series	S14-LED
Input Voltage	120V AC, 60Hz
Colors	3000K
Wattage	1.5W
IP Rating	IP45
Dimmable	10-100%*
Rating	Suitable for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply

Ordering Information

S14-LED-WW	Transparent / Warm White 3000K / 34Lm
-------------------	---------------------------------------

Features

- Only 1.5 watts per bulb - 7 LED diodes per bulb with transparent faceted lens
- E26 nickel base with durable plastic lens cover resists breakage, corrosion, and fading
- Dimmable with most CL or TRIAC dimmers*
- Suitable for indoor/outdoor use
- Sold in boxes of 25

Available CCT



3000K

Listing / Ratings

- Indoor/outdoor use

Dimming Options

- CL
- TRIAC