











Technical Information

Series	NV5 NV7
Input Voltage	120-277V AC, 60Hz
CCT	3000K
CRI	90+
Wattage	10W 15W 20W (Battery Back-up)
Lumens	Up to 750Lm (5") Up to 1200Lm (7")
Beam Angle	120°
Dimmable	TRIAC 10-100% 0-10V Dimming
Mounting	Surface Mount
Rating	cETLus Listed Suitable for wet locations
Rated Life	50,000 hrs
	-

Ordering Information

NV5-30-WH	NIEVE 5" - White 3000K 750Lm 10W TRIAC
NV5-0 10V-30-WH	NIEVE 5" - White 3000K 750Lm 10W 0-10V
NV7-30-WH	NIEVE 7" - White 3000K 1200Lm 15W TRIAC
NV7-0 10V-30-WH	NIEVE 7" - White 3000K 1200Lm 15W 0-10V
NV7-BB-WH	NIEVE 7" - Battery Back-up Accessory (non-dimmable)
NV7-BB-WH-BC	NIEVE 7" - Battery Back-up Accessory (blank cartridge)

Features

- Excellent color rendering (90+ CRI)
- · Modern surface mount design
- Up to 1200 lumen output performance
- 3000K color temperature with 90+ CRI
- Available in 5" and 7" fixture sizes
- Surface mount installation to most standard 1-1/2" deep octagonal junction boxes
- Battery back-up accessory available
- Dimmable with most TRIAC dimmers
- cETLus Listed for wet locations
- 50,000 hours rated life
- ENERGY STAR certified

Available Finishes



White

Dimming Options

- TRIAC (10-100%)
- 0-10V

Listing | Ratings







NIEVE Series Downlights



NIEVE 5 SURFACE MOUNT

NV5-30-WH (120-277V | 3000K | 750Lm | 10W | TRIAC) **NV5-0|10V-WH** (120-277V | 3000K | 750Lm | 10W | 0-10V)



NIEVE 7 SURFACE MOUNT

NV7-30-WH (120-277V | 3000K | 1200Lm | 15W | TRIAC) **NV7-0|10V-WH** (120-277V | 3000K | 1200Lm | 15W | 0-10V)



NIEVE 7 BATTERY BACK-UP ACCESSORY

NV7-BB-WH 120-277V AC | Non-Dimmable (Requires NV7 Light Fixture) NV7-BB-WH-BC Battery Backup Blank Cartridge