































### **Features**

- Up to 330 lumens per foot and 90+ CRI for 3000K, 4000K, and 5000K reels
- 120V AC reels consume only 4 watts per foot
- Dimmable with most CL and ELV dimmers
- Cuttable<sup>+</sup> every 4"
- Economical for larger installations no need for a driver (164ft max run)
- cETLus Listed<sup>†</sup>
- · Suitable for indoor and outdoor use
- 30,000 hours rated life

### Available CCT







3000K 4000K 5000K

# Dimming Options

- CL (10-100%)
- ELV (10-100%)

## Listing / Ratings











## Hybrid 3 Reels


Superb light output for indoor and outdoor use. Parallel wiring in 4" cutting increments ensures that if one LED goes out, the rest of the LEDs continue to operate. Offering up to 330 lumens per foot, Hybrid 3 takes a noticeable jump in brightness over the previous version, making it an effective and energy efficient option for hospitality, home theater, and other various entertainment applications.

### Technical Information

Series	120-H3			
Input Voltage	120V AC			
CCT	3000K / 4000K / 5000K			
CRI	90+			
Wattage	4W per ft			
Lumens	Up to 330Lm per ft			
Max Run	164 feet (50m) (not recommended to exceed 75 feet in any single run)			
Cuttable	Every 4" (101.6mm)			
IP Rating	IP65**, Wet Locations			
Dimmable	10-100%*			
Rating	cETLus Listed† for indoor/outdoor use, Wet locations			
Rated Life	30,000 hrs			

<sup>\*</sup>Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with wall dimmers.

<sup>‡</sup>Do not install in inclement weather or extreme temperature conditions (i.e. -25°C (-13°F) and below)



<sup>\*\*</sup>IP65 rated only when used with pre-attached molded power cord and end cap is either pre-attached or properly sealed with dielectric grease & silicone.

<sup>†</sup>ETL Listing is void if product is cut.





#### HYBRID 3 BULK REELS ORDERING INFORMATION

ITEM NUMBER	ССТ	LENGTH	LUMENS / FT	WATTAGE / FT	IP RATING	CRI	CUTTING
120-H3-30	3000K	150 ft	315Lm / ft	4W / ft	IP65	90+	4" (102mm)
120-H3-40	4000K	150 ft	320Lm / ft	4W / ft	IP65	90+	4" (102mm)
120-H3-50	5000K	150 ft	330Lm / ft	4W / ft	IP65	90+	4" (102mm)

120V Hybrid 3 Bulk Reels Include: (1) 150ft reel of Hybrid 3 / (1) 5ft Attached Power Cord / (4) 120-H3-CONKIT (1) Attached End Cap / (50) Clear plastic mounting clips with screws

HYBRID 3 BULK REELS ACCESSORIES				
ITEM NUMBER	DESCRIPTION			
120-H3-CONKIT	Power connection kit w/Plug			
120-H3-JUMP.5	6" linking cable			
120-H3-JUMP3	3' linking cable			
120-H3-JUMP6	6' linking cable			
120-H3-SPL	In-line splice			
120-H3-END	End cap			
120-H3-CLIPS	Mounting clips (qty 10)			
120-H3-SCLIPS-22	Saddle Mounting clips (qty 22)			
120-H3-CHAN-3	1m aluminum channel			
120-H3-CHAN2-3	1m aluminum deep channel with lens			



120-H3-SPL



120-H3-CONKIT

120-H3-JUMP.5 120-H3-JUMP3 120-H3-JUMP6

120-H3-END





120-H3-CLIPS

120-H3-SCLIPS-22

120-H3-CHAN-3