



Features

- Line voltage - no drivers needed
- Interconnectable kits (3000K Warm White)
- LED Flexbrite consumes only 1 watt per foot
- Dimmable 5-100%*
- UL Listed† for indoor and outdoor use
- 60,000 hours rated life

Available CCT



3000K

Dimming Options

- ELV (5-100%*)
- LED (5-100%*)
- CL (5-100%*)

Listing / Ratings†



LED Flexbrite Kits

Easy to use flexible, dimmable, and economical LED rope light has UV inhibitor built into the PVC housing for use outdoors. Save 73% in running costs compared to incandescent rope light. LED Flexbrite lasts up to three times as long as incandescent rope.


Technical Information

Series	LR-LED (Kits)
Input Voltage	120V AC, 60Hz
CCT	3000K
CRI	72+
Wattage	1W per ft
Lumens	32Lm per ft
Max Run	192 feet (kits)
Cuttable	N/A†
IP Rating	IP65** (uncut), void if cut
Dimmable	5-100%*
Rating	UL Listed† for indoor/outdoor use
Rated Life	60,000 hrs

*Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with wall dimmers.

**IP65 rated only when used with pre-attached molded power cord and end cap is either pre-attached or properly sealed with dielectric grease, silicone and shrink tube

†UL Listing is void if product is cut



Warm White Kits
120V / 3000K / 72CRI / 32Lm/ft / 1/2" Diameter

FLEXBRITE KITS ORDERING INFORMATION

ITEM NUMBER	CCT	LENGTH	LUMENS / FT	WATTAGE	IP RATING	CRI	CUTTING
LR-LED-WW-3	3000K	3 ft	32Lm / ft	3W	IP65	67+	N/A
LR-LED-WW-9	3000K	9 ft	32Lm / ft	9W	IP65	67+	N/A
LR-LED-WW-15	3000K	15 ft	32Lm / ft	15W	IP65	67+	N/A
LR-LED-WW-30	3000K	30 ft	32Lm / ft	30W	IP65	67+	N/A
LR-LED-WW-75	3000K	75 ft	32Lm / ft	75W	IP65	67+	N/A

120V Kits Include: (1) Removable 5ft power cord with 1.6A inverter, (1) removable end cap, and (1) mounting clip per foot of rope

FLEXBRITE KITS ACCESSORIES

ITEM NUMBER	DESCRIPTION
LR-LED-EXT3	3' linking cable
RL-TRACK-4	4' clear plastic mounting track
RL-CLIP/SCREW	Clear plastic mounting clips (qty 10)
LR-CLIP-20	Clear plastic mounting clips (qty 20)



LR-LED-EXT3



RL-TRACK-4



RL-CLIP/SCREW
LR-CLIP-20