



Features

- Die-cast zinc magnesium rough-in housing with durable painted finish and three 1/2" NPS knock-outs with plugs
- Sturdy plastic, fully sealed light module with built-in driver for AC input
- 3000K color temperature
- Choose from a classic faceplate style in two popular finishes
- cETLus Listed
- 30,000 hours rated life

Available Finishes



Stainless Dark Bronze

Listing | Ratings



Brick Light - 100-277V

Line voltage (100-277V) version of the classic brick light with Warm White LEDs available in one style and two finishes. Metal rough-in housing has integrated rubber gasket, threaded knockouts and built-in ground wire. Two faceplate options are available. Each includes an Allen/hex wrench and tamper proof screws for vandal resistance, and matching screw covers for a finished look.

Technical Information

Series	BB2
Input Voltage	100-277V AC, 60Hz
CCT	3000K
CRI	70+
Wattage	2W @120V/3.3W @277V
Lumens	135Lm (Light Module)
Beam Angle	N/A
Dimmable	Non-Dimmable
Mounting	Recessed mount
Rating	cETLus Listed (wet location)
Rated Life	30,000 hrs

Ordering Information

BB2-HSG	Brick Lighting Rough-in Housing (required)
BB2-LED-WW	Brick Light Module 100-277V 3W 3000K 135Lm
BB2-HL-SS	Horizontal Louver Faceplate - Stainless
BB2-HL-DB	Horizontal Louver Faceplate - Dark Bronze

Brick Light Modules



BRICK LIGHT ROUGH-IN HOUSING
BB2-HSG



3000K LED MODULE
BB2-LED-WW (100-277V | 3W | 135Lm)

Brick Light Faceplates



HORIZONTAL LOUVER - STAINLESS
BB2-HL-SS



HORIZONTAL LOUVER - DARK BRONZE
BB2-HL-DB

SPEKTRUM+

TRULUX

TASK LIGHTING

DOWNLIGHTING

12V AC

LINEAR LIGHTING

ARCHITECTURAL

POWER SUPPLIES