



## Features

- Available in E26, E17, and E12 base options
- Formulated PVC sockets form a tight seal around bulbs to preclude the entrance of water and moisture
- Suspended socket has T-mold with mounting hole; Non-suspended socket has two mounting ears built into the base
- Use Commercial Grade Light String with Long Life Pro Decorative lamps (sold separately)

## Available Colors



Black

## Listing / Ratings



LS2 Only



## Commercial Grade Light String

Use Commercial Grade Light String in reels, interconnectable kits, or cord and plug sets with three socket size and spacing combinations for decorative/event/festive lighting applications. Suitable for outdoor, year-round use. For spans up to 20 feet, use eye bolts and plastic ties to anchor ends. For spans longer than 20 feet, use catenary cable (sold separately) with plastic ties at each socket.

## Technical Information

Series	LS / LS2*
Input Voltage	120V AC, 60Hz
Wattage	Max per socket: 25W (E26) / 10W (E17 / E12)
Max Run	See individual product
Socket	E26 (medium)   E17 (intermediate)   E12 (candelabra)
Spacing	24" (E26) / 15" (E17) / 12" (E12)
Cuttable	Yes**
IP Rating	IP64**
Rating	Indoor/Outdoor; Suitable for year-round use*
Rated Life	Varies by lamp used

\* All LS products are non-rated; LS2 interconnectable kits are cTUVus Listed to UL standard UL588 for wet location all-year use, however safety rating is void if product is cut. Not intended for installation in ceilings, soffits, cabinets or other enclosed spaces.

\*\*For non-cut cTUVus Listed LS2 product, interconnected strings must be properly sealed and strain relief protected with electrical tape at each connection point. For non-rated LS product, any cut ends must be sealed with LS-M/MS-END and/or electrical tape (ensure proper seal to preclude entrance of water).

## Light String Accessories

<b>LS-M/MS-END</b>	Plastic End Cap (LS2 /LS)
<b>M-PLUG-BK-SPT2-B</b>	SPT-2 Slide On Male Plug (E17 / E12) - Qty 25



**MEDIUM BASE (E26) cTUVus LISTED ORDERING INFORMATION**

1200W Max (48ft)

ITEM NUMBER	LENGTH	SOCKETS	SOCKET SPACING	SOCKET TYPE	MAX WATTAGE	IP RATING	Rating
<b>LS2-M-24-48-BK</b>	48 ft	24	24 in	Non-suspended	25W per socket	IP64	TUV
<b>LS2-MS-24-48-BK</b>	48 ft	24	24 in	Suspended	25W per socket	IP64	TUV

\* LS2 interconnectable kits are cTUVus Listed for wet location use; safety rating is void if product is cut. LS2 kits include 120V male plug + female socket.

**MEDIUM BASE (E26) ORDERING INFORMATION**

600W Max (48ft) / 1250W Max (100ft) / 1800W Max (330ft)

ITEM NUMBER	LENGTH	SOCKETS	SOCKET SPACING	SOCKET TYPE	MAX WATTAGE	IP RATING	Rating
<b>LS-M-24-100-BK</b>	100 ft	50	24"	Non-suspended	25W per socket	IP64	N/A
<b>LS-M-24-BK</b>	330 ft	165	24"	Non-suspended	25W per socket	IP64	N/A
<b>LS-MS-24-100-BK</b>	100 ft	50	24"	Suspended	25W per socket	IP64	N/A
<b>LS-MS-24-BK</b>	330 ft	165	24"	Suspended	25W per socket	IP64	N/A

\* All LS products are non-rated. 100ft lengths include 120V plug + terminated end. 330ft Bulk reels include bare wire lead + bare wire tail.



**INTERMEDIATE BASE (E17) BULK REELS ORDERING INFORMATION**

1200W Max (330ft)

ITEM NUMBER	LENGTH	SOCKETS	SOCKET SPACING	SOCKET TYPE	MAX WATTAGE	IP RATING	Rating
<b>LS-I-15-BK</b>	330 ft	264	15"	Non-suspended	10W per socket	IP64	N/A

\* All LS products are non-rated. 330ft Bulk reels include bare wire lead + bare wire tail.



**CANDELABRA BASE (E12) BULK REELS ORDERING INFORMATION**

1200W Max (330ft)

ITEM NUMBER	LENGTH	SOCKETS	SOCKET SPACING	SOCKET TYPE	MAX WATTAGE	IP RATING	Rating
<b>LS-C-12-BK</b>	330 ft	330	12"	Non-suspended	10W per socket	IP64	N/A

\* All LS products are non-rated. 330ft Bulk reels include bare wire lead + bare wire tail.