

Catenary Cable

Multi-purpose cable with cable locks for quick, reliable support up to 330 pounds of load and spans up to 110 feet. Order catenary wire in kits, which include the cable locks for each end or in bulk (500ft roll, cable locks sold separately).



Catenary Cable Tensioning Tool
Features internal torque gauge controls



Heavy Duty Cable Lock
Rated up to 330Lbs Loads

Technical Information

Series	LS-CABLE
Max Weight Rating	330Lbs (heavy duty locks)
Rating	Suitable for indoor/outdoor use
Cable Dimensions	1/8" (3mm) Dia. Galvanized Cable

Ordering Information

LS-CABLE-60	60ft Kit / Includes 2 Heavy Duty Cable Locks (330lbs rating)
LS-CABLE-110	110ft Kit / Includes 2 Heavy Duty Cable Locks (330lbs rating)
LS-CABLE-500S	500ft Catenary Cable Bulk Reel
LS-LOCK-4	4-Pack Heavy Duty Cable Locks
LS-TT	Tensioning Tool

Catenary Cable Kits include: (2) Heavy Duty Cable Locks / (1) Cable Release Key

Features

- Provides support for spans of Commercial Grade Light String, Festoon Light String, and other linear lighting products
- 1/8" diameter outdoor rated, galvanized cable and clips resist corrosion
- Cable fasteners can be attached without the use of tools and can be adjusted quickly and easily
- Tensioning Tool allows you to tension wire up to 880lbs with minimal effort due to the 6:1 gear drive mechanism
- The integral torque gauge controls the load applied to the wire, giving consistent tension every time and optimizing the life of the wire

Listing / Ratings



Filament S14

Combine classic style with modern reliability and energy savings with our new Filament S14 LED Light Bulbs. Featuring innovative LED technology with traditional filament style strip, they provide a natural lighting experience for those that want the benefits of LED's and the look of a traditional bulb in your string lighting applications.



Technical Information

Series	S14
Input Voltage	120V AC 12V DC
CCT	3000K
CRI	80+
Wattage	1W (120V AC) 1.9W (12V DC)
Lumens	Up to 90Lm
IP Rating	IP45
Dimmable	10-100%
Rating	cULus Listed
Rated Life	10,000 hrs

Ordering Information

S14-LEDF-12VDC-30K	12V DC Filament S14 / 3000K / 1.9W / Glass
S14-LEDF-120-30K	120V Filament S14 / 3000K / 1W / Glass
S14-LEDF-PET-12AC-30K	12V AC / DC Filament S14 / 3000K / 1.9W / Plastic
S14-LEDF-PET-120V-30K	120V Filament S14 / 3000K / 1.1W / Plastic

Features

- Classic filament style LED powered S14 Bulb
- E26 Medium base with transparent glass lens
- Dimmable with most CL and TRIAC dimmers
- 120V line voltage & 12V DC low voltage bulb options
- 1W per bulb - 10,000 hour rating
- cULus Listed for indoor and outdoor locations
- Sold in boxes of 25

Available CCT



3000K

Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



Pro Dec S14

A variety of LED S14 lamps for direct replacement of 11W incandescent versions saves 87% in running costs. The classic decorative bulb shape features a nickel base which resists corrosion and offers up to 60 lumens of long lasting, energy efficient LED light.



Technical Information

Series	PS14
Base	E26
Input Voltage	120V AC, 60Hz
CCT	2400K / 2700K / 5500K
Wattage	1.4W
Lumens	Up to 48Lm (see individual product)
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply


Ordering Information

PS14-E26-UWW	Transparent / Ultra Warm White (2400K) / 30Lm
PS14-E26-WW	Transparent / Warm White (2700K) / 36Lm
PS14-E26-WH	Transparent / Bright White (5500K) / 48Lm

Features

- SMD LED powered by on-board driver for 120V AC use in medium base (E26) sockets
- Nickel base resists corrosion
- Ultra clear glass lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor and outdoor use
- Sold in boxes of 25

Available CCT



Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



Pro Dec G50

Spherical LED G50 (50mm diameter) lamps for direct replacement of 10W incandescent versions, saving 86% in running costs.



Technical Information

Series	PG50
Base	E26
Input Voltage	120V AC, 60Hz
CCT	2400K / 2700K
Wattage	1.4W
Lumens	Up to 36Lm (see individual product)
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply


Ordering Information

PG50-E26-UWW	Transparent / Ultra Warm White (2400K) / 30Lm
PG50-E26-WW	Transparent / Warm White (2700K) / 36Lm

Features

- SMD LED powered by on-board driver for 120V AC use in medium base (E26) sockets
- Nickel base resists corrosion
- Available in transparent and opaque lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor/outdoor use
- Sold in boxes of 25

Available CCT



Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings

