## 19. SOURCE CAPTURE ARMS, BOOM/PAC

# PAC SERIES Pivoting Articulated Crane (shown with 15000 Arm) PAC length: 10', 15', 20' Allows for versatile positioning, with accessories (welding arm shown), at any point with extended radius PAC has full pivoting wall/column bracket and center pivoting joint Mount bracket is one-piece die-stamped 5/16" industrial plate Horizontal sections of PAC constructed of 2" x 4" tubular steel, joined by a heavy-gauge pivoting pin, allowing for easy and free movement

### SB SERIES Swivel Boom (shown with 15000 Arm)

- Boom length: 7', 10', 13'
- One piece pivoting extension
- Many options attach to swivel boom, including 15000 arm, and more
- Boom supplied with pivoting wall/column bracket constructed of one-piece die, stamped 5/16" industrial steel plate
  - The sections are welded together using vertical tubular sections



# 15000-EXT SERIES External Support Arm

- External support arm: lengths range from 5' to 36'
- 4", 5", 6" or 8" Diameter
- Package includes: blower (optional), wall/column
- mounting bracket, arm, exter-nal support structure, and polycarbonate hood with handle
- Three adjustable pivot points
- Optional light kit available



### MNX SERIES Mini Arm

- Mini Arms may be used in a vast array of applications ranging from soldering to graphic arts. Mini Arms may be wall mounted, mounted directly to duct, or mounted to tables
- Ideal for removal of toxic fumes and odors in laboratory or shop environments
- Various nozzle and hood options are available, including: clear dome hoods, metal hoods, angle cut suction nozzles, and flat flange hoods '

• Available in 2", 3", 4"

