

# WELL Fit

## FEATURES

- A completely wireless IP65 rated battery powered up-light with four high powered quad colored RGBA LEDs that is controlled by W-DMX or IR remote.
- Chrome exterior for blending into its surroundings.
- Ships with 6 slot drop in charging case for easy storage and re-charging of the battery.
- 8 hours of operation at full and a quick 5 hours charging time for frequent use.
- Built in automated programs recallable by IR, WDMX or manually.
- M12 threaded insert for easy clamp installation and a Kensington lock position for securing your investment.



## SPECIFICATIONS

### OPTICAL

- Light Source: 4 LEDs (quad- color RGBA) 10 W, (720 mA), 50,000 hours life expectancy).
- Beam Angle: 10.8°
- Field Angle: 19.6°
- Illuminance (19.6°): 988 lux @ 5 m
- PWM Frequency: 1200 Hz

### DYNAMIC EFFECTS

- Color Macros: 5 macros
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 24 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

### CONSTRUCTION / PHYSICAL

- Dimensions: 5.4 x 5.7 x 8 in (138 x 145 x 202 mm)
- Dimensions (charging case): 20.4 x 18.5 x 21.2 in (519 x 470 x 540 mm)
- Weight (single unit) 7.4 LB (3.4 kg)
- Weight (charging case): 103.6 lb (47 kg)
- Exterior Color: Chrome
- Housing Material: Aluminum die-cast

### CONNECTIONS

- Power Connection: Edison (Local) plug to Neutrik® powerCON
- Power Input: Neutrik® powerCON®
- Cable Length (power): 5 ft (1.5 m)

### CONTROL

- Control Protocol: W-DMX™, IRC
- DMX Channels: 3, 4, 6 or 10
- Modes/Personalities: 5 personalities (4Ch, 6Ch, 10Ch, HSV, HSI)

## ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 4 units @ 120 V; 7 units @ 208 V; 8 units @ 230 V
- Power and Current (single unit charging): 60 W, 0.641 A @ 100 V, 60 Hz
- Power and Current (charging case): 345 W, 3.323 A @ 100 V, 60 Hz
- Power and Current (single unit charging): 58 W, 0.535 A @ 120 V, 60 Hz
- Power and Current (charging case): 334 W, 2.750 A @ 120 V, 60 Hz
- Power and Current (single unit charging): 51 W, 0.363 A @ 208 V, 60 Hz
- Power and Current (charging case): 322 W, 1.584 A @ 208 V, 60 Hz
- Power and Current (single unit charging): 54 W, 0.342 A @ 230 V, 50 Hz
- Power and Current (charging case): 317 W, 1.422 A @ 230 V, 50 Hz
- Power and Current (single unit charging): 54 W, 0.335 A @ 240 V, 50 Hz
- Power and Current (charging case): 311 W, 1.363 A @ 240 V, 50 Hz

## BATTERY

- Battery type: Lithium Ion
- Rechargeable: Yes
- Battery Charge Time: 5 hours
- Battery Life: (all on) 8 hours, (single LED) 20 hours
- Battery Power: 14.8 V, 11 Ah

## CERTIFICATIONS / QUALIFICATIONS

- CE, UKCA
- IP Rating: IP65, temporary outdoor/wet use

## WHAT'S INCLUDED

- WELLFITX6
- (6) WELL FIT
- (1) Charging case
- (1) IR remote
- (1) powerCON power cable with Edison plug
- (1) QRG
- (1) Warranty card

## OPTIONAL ACCESSORIES

- [Clamps](#)
- [WDMX MicroT-1 TRX G6](#)