

Ovation P-56UV

FEATURES

- True (365 nm) UV light with homogenized single source
- Minimal projected visible light
- Quiet operation for use in any situation with fan speed control
- RDM and variable Pulse Width Modulation for setup ease
- Accepts standard 7.5" beam shaping accessories
- Selectable dimming curves for smooth fades or snap-on use
- 16-bit dimming resolution for smooth fades
- Compact design with homogenous single source of backlight



SPECIFICATIONS

OPTICAL

- Light Source: 1 LEDs (1UV) 114 W, (3 A), 50,000 hours life expectancy
- Coverage Angle (Wide Lens): 56°
- Radiant Power: 33022mW
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 29 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 12.48 x 12.83 x 14 in (317 x 326 x 363 mm)
- Weight: 12 lb (5.4 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast
- Accessory Holder/Gel Frame Size: 7.5 in (191 mm)

CONNECTIONS

- Power Connection: Edison (Local) plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Power Output: Neutrik powerCON
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 1, 2, 3 or 6
- Modes/Personalities: 4 personalities (1, 2, 3, 6)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 13 units @ 120 V; 21 units @ 208 V; 23 units @ 230 V
- Power and Current: 125 W, 1.03 A @ 120 V, 60 Hz
- Power and Current: 130 W, .62 A @ 208 V, 60 Hz
- Power and Current: 136 W, .58 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC
- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- Ovation P-56UV
- [Neutrik powerCON power cord](#)
- Gel frame holder (7.5 in/191 mm accessories)

OPTIONAL ACCESSORIES

- Professional Clamps: [CTC-50HC](#), [CTC-50HCN](#)
- [Neutrik® powerCON® cables](#)
- 3-pin or 5-pin DMX Cables
- Ovation F 7.5" Barndoor
- DF60X1D – 60x1 deg Color Blending Filter