

# CONTROL4® PLUG-IN OUTLET DIMMER AND SWITCH



**CONTROL4® PLUG-IN OUTLET DIMMER** C4-V-ODIM120  
**CONTROL4® PLUG-IN OUTLET SWITCH** C4-V-OSW120

Intelligent lighting is an essential part of every smart home and provides added convenience and peace of mind. The Control4 Wireless Plug-In Dimmer and Switch are additions to the Control4 Wireless Lighting product line and are designed with the essential features enabling them to be included with every Control4 system. The Control4 Plug-In Outlet Dimmer and Switch easily plug into outlets to offer complete control of your plug-in lights. Control4 smart lighting control solutions are accessible to everyone and let you add rooms and functions when it makes sense for you.

- Never come home to a dark house again
- Your home looks lived in when you are away
- Set the perfect lighting-level for everything—romantic dinners, parties, relaxing, cleaning
- Reduce energy waste and lower your utility bills by setting lights for maximum energy efficiency
- Turn standard outlets into a smart way to control two plug-in lamps or other devices—no special wiring required

# CONTROL4® PLUG-IN OUTLET DIMMER AND SWITCH

	<u>Model</u> Control4 Plug-In Outlet Dimmer	<u>Model</u> Control4 Plug-In Outlet Switch
<u>Model number</u>	C4-V-ODIM120	C4-V-OSW120
<u>Power</u>		
Power requirements	120V AC +/- 10% 60 Hz	120V AC +/- 10% 60 Hz
Power consumption	3.6W	3.6W
<u>Load</u>		
Outlets	2 outlets controlled together	2 outlets controlled together
Supported load types	Incandescent/tungsten/halogen—300W, dimmable compact fluorescent—150W, and dimmable LED—150W (load ratings are for both outlets combined)	Incandescent/tungsten/halogen—600W (1800W resistive) and motor—15A resistive, 1/2 HP (load ratings are for both outlets combined)
<u>Control</u>		
Control communications	Zigbee (802.15.4) Mesh Networking	Zigbee (802.15.4) Mesh Networking
<u>Environmental</u>		
Operational temperature	0 °C to 40 °C (32 °F to 104 °F)	0 °C to 40 °C (32 °F to 104 °F)
Humidity	5% to 95% non-condensing	5% to 95% non-condensing
Storage	-20 °C to 60 °C (-4 °F to 140 °F)	-20 °C to 60 °C (-4 °F to 140 °F)
<u>Physical</u>		
Dimensions (H × W × D)	74 × 99 × 38 mm (2.9 × 3.9 × 1.5")	74 × 99 × 38 mm (2.9 × 3.9 × 1.5")
Weight	181 g (0.4 lb)	181 g (0.4 lb)
Available colors	WH	WH

MOST RECENT VERSION



[ctrl4.co/osw120-ds](http://ctrl4.co/osw120-ds)

INSTALLATION GUIDE, DIMMER



[ctrl4.co/c4-v-odim120-ig](http://ctrl4.co/c4-v-odim120-ig)

INSTALLATION GUIDE, SWITCH



[ctrl4.co/c4-v-osw120-ig](http://ctrl4.co/c4-v-osw120-ig)