

# Rogue Outcast 2X Wash

## FEATURES

- Fully featured IP65 rated RGBW LED yoke wash fixture
- Durable and lightweight aluminum/magnesium alloy body
- Smooth fades with 16-bit individual color and master dimming
- 8° to 66° zoom
- 19 RGBW LEDs, 25W each
- 5-pin DMX input/output connections
- 5 zones of LED control for pixel mapping control
- Fast, smooth pan and tilt movement
- RDM enabled for remote addressing and trouble shooting
- Selectable PWM options for camera operation
- User selectable calibrated white, 7500K default calibration
- 6 distinct dimming modes for advanced control
- Easy to read OLED display with simple, effective menu options
- Simple and complex DMX channel profiles for programming versatility
- USB-C port for uploading software



---

## SPECIFICATIONS

### OPTICAL

- Light Source: 19 LEDs (quad-color RGBW) 25 W, (1.5 A), 50,000 hours life expectancy
- Color Temperature (range): 2800 to 10000 K
- Beam Angle: 8° to 36.1°
- Field Angle: 11.8° to 53°
- Cutoff Range: 17.5° to 66.1°
- Zoom Range: 8° to 66.1°
- Lumens – Source: n/a
- Lumens – Output: 6,258
- Illuminance (11.8°): 8,713 lux @ 5 m
- Illuminance (53°): 694 lux @ 5 m
- Selectable PWM: 600Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

### DYNAMIC EFFECTS

- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Motorized
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Curves: 6

- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No

## CONSTRUCTION / PHYSICAL

- Dimensions: 11.92x8.58x14.1" (303x218x361mm)
- Weight: 23.4 lb (10.6 kg)
- Exterior Color: Black
- Housing Material: Aluminum/magnesium alloy, High-impact flame-retardant polymer

## CONNECTIONS

- Power Connection: Bare ended to Seetronic IP65 PowerKon
- Power Input: Seetronic IP65 PowerKon
- Power Output: Seetronic IP65 PowerKon
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

## CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 15, 17, 22, 33, 54, or 56
- Modes/Personalities: 8 personalities (15CH, 17CH, 22CH, 33CH, 33CH MS, 54CH, 54CH MS or 56CH)

## ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 5 units @ 120 V; 9 units @ 208 V; 10 units @ 230 V
- Power and Current: 291 W, 2.47 A @ 120 V, 60 Hz
- Power and Current: 284 W, 1.41 A @ 208 V, 60 Hz
- Power and Current: 282 W, 1.28 A @ 230 V, 50 Hz

## CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC, UKCA
- IP Rating: IP65 (temporary wet location)

## WHAT'S INCLUDED

- Rogue Outcast R2X Wash IP
- Seetronic® powerCON® power cord

## OPTIONAL ACCESSORIES

- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-07
- Seetronic IP65 PowerKon cables
- DMX Cables
- Flight Case: CP6CASER2W