

STRIKE 4

FEATURES

- 16-bit dimming control for smooth, perfect fades
- Individual pan of each head to allow for directional adjustment of light output
- Simple and complex DMX channel profiles for programming flexibility
- Easy to use OLED display
- Automated strobing programs for easy programming
- Adjustable Pulse Width Modulation (PWM) control to eliminate flicker on camera

SPECIFICATIONS

OPTICAL

- Light Source: 4 LEDs (WW) 100 W, (2.3 A), 3096 K, 50,000 hours life expectancy
- Color Temperature (at full): 3096 K
- Beam Angle: 49°
- Field Angle: 79°
- Illuminance (total): 999 lux @ 5 m
- Illuminance (per cell): 242 lux @ 5 m
- Pixels: 2 x 2
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Pan: $\pm 24^\circ$ manual adjustment per pod
- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 30 Hz
- Standalone Color Mixing: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 14.2 x 6.4 x 14.2 in (362 x 163 x 362 mm)
- Weight: 19 lb (8.7 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

CONNECTIONS

- Power Connection: Edison (Local) plug to Neutrik powerCON
- Power Input: Neutrik powerCON
- Power Output: Neutrik powerCON
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX



- DMX Channels: 1, 3, 4 or 9

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 5 units @ 120 V; 9 units @ 208 V; 10 units @ 230 V
- Power and Current: 301 W, 2.49 A @ 120 V, 60 Hz
- Power and Current: 287 W, 1.43 A @ 208 V, 60 Hz
- Power and Current: 286 W, 1.29 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE
- IP Rating: IP20, dry location

WHAT'S INCLUDED

- STRIKE 4
- [Neutrik powerCON power cord](#)

OPTIONAL ACCESSORIES

- Professional Clamps: [CTC-50HC](#), [CTC-50HCN](#)
- Safety Cable: [SC-07](#)
- [Neutrik powerCON cables](#)
- [DMX Cables](#)