



Ready to

REMOVE


TECHNICAL SPECIFICATIONS
BeachTech 1000




BeachTech®



BeachTech 1000

 **Engine power**
from 25 kW | 35 hp

 **Working width**
1.250 mm

 **Hopper volume**
0,4 m³

 **Area coverage**
up to 10.000 m²/h



| | | |
|---|--|---------------------------------------|
| Cleaning method | Screening technique with vibrating screen and transport system | |
| Tractor requirements | Engine power min.** | 25 kW (35 hp) |
| | Four-wheel drive | |
| | differential lock | |
| | 3-point hitch, cat. 1 or cat. 2 | |
| | PTO shaft | Z6,1 3/8" |
| | power take-off, AR NORM | 540 rpm |
| | power supply | 12 V |
| | Dimensions | vehicle length, road transport |
| vehicle width, road transport | | 1.750 mm |
| working width | | 1.250 mm |
| vehicle height | | 1.800 mm |
| Unloading height collecting hopper | | 0 - 1.600 mm |
| Tires | low pressure tires, wide | 24 x 13.00 - 12 |
| Weight | Empty weight | 1.220 kg |
| | Technically permissible total weight* | 2.000 kg |
| Tank capacity | hydraulic oil | 70 l |
| Performance | area coverage up to** | 10.000 m ² /h |
| Working depth | working depth up to** | 10 cm |
| Capacity | collecting hopper | 0,4 m ³ |
| Speed | operating speed max.** | 8 km/h |
| | road traffic* | 25 km/h |

* according to local traffic regulations

** depending on soil / beach conditions

Subject to change in the course of technical development. The images shown are for illustration purposes only and may contain optional extras.

dealer stamp

BeachTech®

Tel.: +49 7392 900 - 461
E-Mail: info@beach-tech.com
www.beach-tech.com