

Swing-Out™ Valve Accessories & Pyrolite Swing-Out Valve

Navigator™ Pro Valve Controller

The Valve Controller from Akron Brass provides reliable and accurate valve control with valve position indication. It is packed with user friendly features that improve operation effectiveness and safety.

9323 Electric Valve Controller

- Valve open and close.
- Full color LCD display visible in bright sunlight.
- True position feedback from the valve.
- User programmable presets.
- Valve name and the discharge color can be programmed on the top bar of the display.
- USB port on-board. Software for display and motor driver can be easily updated via USB flash drive.
- Easy to navigate setup menu.
- Auto dimming capability.
- Multiple display capable. Multiple displays can be used to control the same valve.
- Auto open. When option is turned on and valve is closed, pressing the open button once will automatically open the valve all the way.
- J1939 CAN networked.
- For use only with Navigator Pro Electric Actuator. See page 80 & 81 for Actuator details.



STYLE 9323 Navigator Pro Shown in Closed Position

9325 Navigator Pro Controller

All the same features as the 9323, plus the following:

- Optional pressure display. Can be displayed in psi, kPa or bar*.
- Optional flow display. Can be displayed in gpm or lpm*.
- Optional CAFS integration: turn CAFS on and off*.
- Make sure even the most turbulent of flows is accurate with available custom calibration. Now easier than ever to custom calibrate the flow sensor through an easy to navigate menu.
- Totalizer function. Controller will calculate the volume of water flowed, through the paired valve. Resets every time the power is cycled to the valve. When networked with other 9325 controllers, total flow across all valves is shown.

* Available when flow, pressure or CAFS equipment installed.

Style 9325 Navigator Pro with Pressure and Flow



Optional color indicators available in standard NFPA 1901 specified colors. Available on Styles 9323 and 9325.

Lightweight Pyrolite Apparatus Swing-Out Valve

7725 2 1/2" Lightweight Apparatus Swing-Out Valve

- Ideal for use on aerial platforms
- Durable lightweight Pyrolite® construction
- Full flow 2 1/2" waterway
- Simple two seated design (no O-Rings to cut or lose during assembly or maintenance)
- No lubrication or regular maintenance required
- Designed & tested to exceed NFPA requirements
- Weight 9 3/8 lbs. (4.1 kg)

Adapter Options:

- MES1-S 90° Elbow
- PI-S Female NPT
- M1-S Male
- F1-S Female Swivel
- F1-SS Female Swivel with Strainer



Style 7725