

Clappered Siamese

262 Clapper Valve Siamese

A brass Clapper Siamese with a leather carrying handle and $\frac{3}{4}$ " drain plug

1256 3-Way Clapper Valve Siamese - Pyrolite®

Three $2\frac{1}{2}$ " female inlets x 4" to 6" male or female outlet. Includes Style 4 Drainit drain valve and rubber carrying handle

- 200 psi operating pressure

- Optional Pressure Gauge

1262 Clapper Valve Siamese

A Pyrolite Clapper Siamese includes a Style 4 Drainit drain valve and a rubber carrying handle

1267 Clapper Valve Siamese

A Pyrolite Clapper Siamese includes a Style 4 Drainit drain valve and a rubber carrying handle



Style 262



Style 1256



Style 1262



Style 1267

Style	Material	Length	Width	Weight lbs. (kg)	Inlet	Outlet
262	Brass	7 $\frac{3}{4}$ " (197 mm)	9" (229 mm)	14 $\frac{1}{2}$ (6.6 kg)	(2) 2 $\frac{1}{2}$ " F (65 mm)	2 $\frac{1}{2}$ " or 3" M (65 or 75 mm)
1256	Pyrolite	12 $\frac{3}{4}$ " (323 mm)	14 $\frac{3}{4}$ " (375 mm)	15 $\frac{1}{2}$ (7 kg)	(3) 2 $\frac{1}{2}$ " F (65 mm)	2 $\frac{1}{2}$ " - 6" M or F (65-150 mm)
1262	Pyrolite	8 $\frac{1}{2}$ " (216 mm)	9 $\frac{3}{8}$ " (238 mm)	7 $\frac{1}{4}$ (3.3 kg)	(2) 2 $\frac{1}{2}$ " F (65 mm)	2 $\frac{1}{2}$ " or 3" M (65 or 75 mm)
1267	Pyrolite	9 $\frac{3}{8}$ " (238 mm)	9 $\frac{3}{8}$ " (238 mm)	9 $\frac{1}{2}$ (4.3 kg)	(2) 2 $\frac{1}{2}$ " F (65 mm)	2 $\frac{1}{2}$ " - 6" F, (65-150 mm) 3 $\frac{1}{2}$ " - 6" M, 4" or 5" Storz (89-150, 100 or 125 mm)

* Weight with 4 $\frac{1}{2}$ " (114 mm) outlet

Gated Siamese

Siamese with quarter-turn valves provide a positive shutoff and easier operation. All 2 $\frac{1}{2}$ " swivel inlets are supplied with strainers.

1583 Suction Siamese

Used on pumper suction or aerial platform inlets. Features Tork-Lok® handles for positive handle positioning.

2583 3-Way Suction Siamese

Used on pumper suction or aerial platform inlets. Features Tork-Lok handles for more positive handle positioning.



Style 1583



Style 2583

Style	Material	Length	Width	Weight lbs. (kg)	Inlet	Outlet
1583	Pyrolite®	9 $\frac{1}{4}$ " (235 mm)	11 $\frac{1}{2}$ " (292 mm)	16 * (7.3 kg)	(2) 2 $\frac{1}{2}$ " F (65 mm)	2 $\frac{1}{2}$ " - 6" F or M 4" or 5" Storz (65 - 150 or 100 or 125 mm)
2583	Pyrolite	11 $\frac{3}{4}$ " (298 mm)	16" (298 mm)	26 $\frac{1}{2}$ * (12 kg)	(3) 2 $\frac{1}{2}$ " F (65 mm)	2 $\frac{1}{2}$ " - 6" F or M 4" or 5" Storz (65 - 150 or 100 or 127 mm)

* Weight with 4 $\frac{1}{2}$ " (114 mm) inlet

