HEAVY-DUTY

CARITON 2015 15" DRUM STYLE WOOD CHIPPER

THE PROFESSIONAL'S CHOICE





Powerful Durable Durable Reliable

Carlton's 2015 Apache

15" CAPACITY DRUM STYLE CHIPPER

The Carlton 2015 Apache chipper shares many of the quality design features of its bigger brother - the 2518 - while coming in a smaller, lighter, more compact size.

Aggressive feeding is handled by the exclusive long arm pivot top feed roller. This long arm pivot design keeps the top feed roller close to the drum with a lift path the closely matches the contour of the drum—minimizing the dead space and "hang ups." The dual feed wheels are powered by three hydraulic drive motors working on two independent circuits to further maximize pulling power.

The 2015 Apache utilizes Carlton's exclusive Air Vortex Control to channel and accelerate discharge air, giving the 2015 high discharge velocities and great chip throwing power.



Carlton's Exclusive Air Vortex Control channels and accelerates discharge air giving the Apache series high discharge velocities and great chip throwing power.

Optional Hydraulic Winch



Spring Mounted Steel Tank resists vibration and cracking. Hydraulic filter is mounted inside the tank to avoid damage.

Hand Crank Swivel Discharge quickly and easily allows the operator to fill the largest capacity chip trucks corner to corner, or direct the chips to a









Tandem Pump System provides power independently to each feed wheel. This system ensures the most power at all times to the feed system.



10,000-pound Capacity Dexter Torflex Axle makes the 2015 tow great, while minimizing turf damage.



Hydraulic Winch will accept cable or rope. Winch includes freewheel capability.



Dual Edge Knives are easily accessible, making routine maintenance an easy process. Bolts and Nuts are both removable eliminating problems caused by cross threading or stripping pockets.



Digitally Controlled Reversing Autofeed monitors engine rpm and adjusts the feed automatically. This system has the ability to start, stop, and reverse the feed of the material into the chipper based on parameters set by the operator.

Hand Crank Height Adjustable Discharge Chute allows the operator to quickly adjust the discharge perfectly for any truck.

> 14 Ply Rated Heavy Duty Tires

Tandem Hydraulic System provides hydraulic fluid independently to each feed wheel. This system ensures the most power at all times to the feed system. By running this system directly off the engine, all hydraulic functions are available without engaging the drum.



the sides allows for a full 360-degree

chute rotation.



The Combination of Three Hydraulic Feed Motors, Carlton's exclusive long arm pivot, and the oversized 15¾" top feed roller give the 2015 the best feeding characteristics available.

LED Taillights mounted high on the infeed out of harm's way. The 2015's taillights have heavy-duty covers for extra protection. Wiring is loomed and soldered for added protection and weather resistance.



Massive 20" x 15" Throat Opening is the largest in its class and easily handles the largest tops.

Carlton Quality DURABLE DEPENDABLE



The Carlton 2015 is designed to bridge the gap between standard capacity and massive 18" capacity machines. The 2015 is a great leap in capacity and ability over a 12" disk style machine without paying a penalty in size and weight. The 2015 incorporates a feed system that is stronger and more powerful than competitors 18" machines!!

The 2015 will make your team more productive by minimizing trimming and handling of the wood waste. No more fighting the big tops!!!



CALL TOLL FREE **800-243-9335**VISIT US ON THE WEB AT

www.stumpcutters.com

-AGGRESSIVE
ON CARLTON CARLTON CARLTON CAR VERFUL POW ASSIVE MASSIVE ING CHIPPING CHIP **CAPACITY CAP**

| CARLTON MODEL | 2015 SPECIFICATIONS |
|--------------------------------|---|
| General | |
| Weight | 6820 Pounds |
| Length | 211 inches |
| Height | 100 inches |
| Tires | 235/75R17.5 Ld Rng H 4805 # @125 PSI |
| Axles | Dexter Torflex 10,000 Pound Cap |
| Brakes | Electric with Breakaway Switch |
| Hitch | Five Inch Height Adjustable Pintle |
| Fuel Capacity | 25 Gallons |
| Battery | 29 HVD 950 CCA |
| Jack Stand | 10000 # Cap Screw Type Swing Up |
| Engine | |
| Manufacturer | John Deere |
| Number of Cylinders | Four |
| Bore | 4.19 Inches (106 mm) |
| Stroke | 5.0 Inches (127 mm) |
| Displacement | 276 Cubic Inches (4.5L) |
| Maximum RPM | 2400 RPM |
| Horsepower | 140HP* |
| Torque | 367 Ft Lbs (498 NM) |
| Cooling Medium | Liquid Water/Antifreeze Mixture |
| Air Cleaner | Two Stage Dry Type |
| Oil Filter | Full Flow Spin On |
| Oil Capacity | 13 Quarts |
| Oil Type | John Deere |
| Electrical | 12 Volt |
| Gauges | Powerview |
| Clutch | Twin Disk 11 ½" Over Center |
| Bearings | |
| Drum Bearings | 2 15/16 inches Tapered Roller |
| Feed Roller Bearings | 2 1/16 inches Tapered Roller |
| Drum Shaft | 3 ½ inches |
| Feed Roller Shaft | 2 inches |
| Chipper Drum Drum Diameter | 24 inches |
| | |
| Drum Width w/Fans Disk Balance | 27 inches Precision High Speed Balanced |
| Drum Speed | 2000 RPM Nominal |
| Number of Knives | 2 |
| Knife Dimensions | 10 ½" x 5 ½" x 5%" |
| Anvil | 2" x 20 1/8" x 1/2" AR400 |
| Drum Fans | 12 1/4" x 2 1/2" x 6 3/4" |
| Cutting Dimensions | |
| Throat Opening | 15" x 20" |
| Tilloat Opening | ·- ··-* |

| Due to constant product improvement specifications | | |
|--|--|--|
| subject to change. Contact Carlton for more information. | | |

call toll free **800-243-9335**visit us on the web at **www.stumpcutters.com**



| Hydraulic System | |
|-----------------------|--|
| Hyd Pump Displacement | 1.5 in cu/rev total from 2 pumps |
| Hyd Pump Drive System | Direct Drive off Engine Mount |
| Flow | 16 GPM Total Tandem Systems |
| System Relief | 2500 PSI |
| Oil Tank Capacity | 18 Gallons |
| Oil Type | AW32 |
| Valve | D05 Electric Solenoid |
| Hose | 16,000 PSI Burst - Exceeds SAE 100R2 |
| Oil Filter | 10 Micron Return with Suction Strainer |
| Drive System | To Miloton Hotalin Milit Gudilon Giramon |
| Engine Sheave | 4/5V9.25 |
| Jackshaft Sheave | 4/5V11.80 |
| Drive Belt | 4/5V1120 |
| Cutter Head Shaft | 3 ½ inches |
| Feed System | |
| Feed Motors | 46 In Cu Top Two 32 In Cu Bottom |
| Flow | Separate Systems for Top/Btm Feed |
| Hydraulic Drive | Live – Driven off engine |
| Autofeed | Reversing, Digital, Fully Adjustable |
| Feed Rate | 110 Feet Per Minute |
| Feed Rollers | Top: 15 3/4" Dia Bottom: 10 1/2" Dia |
| Springs | Two 30" Tight Wound Powder Coated |
| Feed Pivot Bearings | Two 2" Tapered Roller |
| Lift Cylinders | Two 2" x 16" with 1" attachments |
| Discharge | Crank Adjustable Swivel and Height |
| Frame | |
| Main Trailer Tongue | 3" x 6" with 3%" wall |
| Main Trailer Frame | 2" x 6" with 1/4" wall |
| Telescoping Tongue | N/A |
| Engine Channel Mnts | 4" Channel with 5/16" web |
| Infeed Chute | 3/16" with 2" x 2" x 1/4" tube frame |
| Infeed Tray | 3/16" Plate w/2" x 2" and 2" x 4" Tube |
| Folding Tray Lock | N/A |
| Discharge Chute | 12 gauge |
| Discharge Lock | 3/4" Spring Loaded Pin |
| Fuel Tank | High Density Polyethylene |
| Hydraulic Tank | 3/16" Steel w/baffles, spring and rubber mounted |
| Battery Box | 10 gauge - lockable |
| Fenders | 3/16" checker plate |
| Feeder Bar | 1 ½" OD x 1/s" wall - removable |
| Radiator Guards | N/A |
| Light Brackets | 3/16" with hidden wiring |
| Hitch Plate | 3/4" Plate adjustable 5" Up/Down |

EXCEPTIONAL QUALITY & CUSTOMER SERVICE



Carlton's commitment to quality can be found in every piece of equipment they manufacture. Each Carlton wood chipper is a result of superior design and the highest quality construction. Plus, Carlton's staff of highly trained and experienced professionals stands behind each wood chipper and is ready with answers to your questions. From parts and service to technical support, Carlton is dedicated to providing the best customer service in the industry. Carlton—Quality products and exceptional service.