



Approvals



Standard Features

- Auto-recomputing function
- Negative sampling and counting (count out of a full container)
- Bright green LED
- Simultaneous weight display, unit weight, tare and quantity
- Net/gross weight display
- Lb/kg weight display conversion
- Full-duplex RS-232 output to PC or printer
- AC or rechargeable battery operation (battery optional)
- Choice of unit weight per thousand or average piece weight
- Remote scale capability
- 100 product look up registers
- NTEP for non-counting applications
- Remote scale interface

Specifications

- Internal Resolution:**
1/1,000,000
- Weight Display Resolution:**
1/5,000 NTEP, other selections capacity dependent
- Display:**
LED
Weight: Five-digit
Unit weight: Five-digit
Quantity: Seven-digit
Tare: Five-digit
- Power Source Consumption:**
AC: 115 VAC, 60 Hz
Optional battery: 6 V, 5.0 Ah
- Printer Compatibility:**
Zebra® GK-421
Zebra GK-421T
Epson® TM-U220 tape
STAR® SP512 tape
Epson® TM-U295 ticket
GoDex® G500

Part Number/Price

| Part # | Description | Weighing Resolution | Platter | Est. Weight | Price |
|----------------------------------------------|------------------------|-------------------------------|--------------------------------------------|-----------------|------------|
| 88928 * | DC-788, 2 lb (1 kg) | 0.0002 lb (0.0001 kg) | 7 × 10 in (178 × 254 mm) | 15 lb (7 kg) | \$875.00 |
| 88929 | DC-788, 10 lb (5 kg) | 0.002 lb (0.001 kg) | 10 × 13 in (254 × 330 mm) | 15 lb (7 kg) | \$875.00 |
| 88930 | DC-788, 25 lb (10 kg) | 0.005 lb (0.002 kg) | 10 × 13 in (254 × 330 mm) | 15 lb (7 kg) | \$875.00 |
| 88931 | DC-788, 50 lb (25 kg) | 0.01 lb (0.005 kg) | 10 × 13 in (254 × 330 mm) | 15 lb (7 kg) | \$875.00 |
| 88932 | DC-788, 100 lb (50 kg) | 0.02 lb (0.01 kg) | 10 × 13 in (254 × 330 mm) | 15 lb (7 kg) | \$1,095.00 |
| Part # | Description | Platter Dimensions | Overall Dimensions | Est. Weight | Price |
| Optional DIGI S-YC Remote Scale Bases | | | | | |
| 154835 | 500 g (1 lb) | 7.9 × 5.6 in (201 × 143 mm) | 13.4 × 11.1 × 3.5 in (341 × 284 × 90 mm) | 7.7 lb (3.5 kg) | \$775.00 |
| 154836 | 1 kg (2 lb) | 9.6 × 6.9 in (244 × 177 mm) | 13.4 × 11.1 × 3.5 in (341 × 284 × 90 mm) | 7.7 lb (3.5 kg) | \$775.00 |
| 154838 | 2.5 kg (5 lb) | 13.4 × 11.1 in (341 × 284 mm) | 13.4 × 11.1 × 4.75 in (341 × 284 × 120 mm) | 11 lb (5 kg) | \$700.00 |
| 154839 | 5 kg (10 lb) | 13.4 × 11.1 in (341 × 284 mm) | 13.4 × 11.1 × 4.75 in (341 × 284 × 120 mm) | 11 lb (5 kg) | \$700.00 |
| 154840 | 10 kg (20 lb) | 13.4 × 11.1 in (341 × 284 mm) | 13.4 × 11.1 × 4.75 in (341 × 284 × 120 mm) | 11 lb (5 kg) | \$700.00 |
| 154841 | 25 kg (50 lb) | 13.4 × 11.1 in (341 × 284 mm) | 13.4 × 11.1 × 4.75 in (341 × 284 × 120 mm) | 11 lb (5 kg) | \$700.00 |

*Non-NTEP

Options/Accessories

| Part # | Description | Price |
|-----------------|------------------------------------------------------------------------|----------|
| 88933 | Rechargeable battery—lead acid type | \$80.00 |
| 73386 | Anti-static sample tray | \$26.00 |
| 32375 | 14-pin load cell connector, Amphenol (remote base, non-DIGI) | \$21.00 |
| 35319 | 14-pin load cell connector with 20 ft cable | \$72.00 |
| 91685 | Additional operating and service manual | \$26.00 |
| 70056 | Nine-pin printer cable to DT4, G500 | \$40.00 |
| 72440 | Nine-pin printer cable to Epson TM-U220/TM-U295 SP512 | \$67.00 |
| 66535 | Nine-pin cable to PC, null modem cable, to be used with Zebra printers | \$46.00 |
| 91214 | AC adapter 110-230 VAC, U.S. plug | \$46.00 |
| Printers | | |
| 212409 | Zebra ZD421D, direct thermal printer. | \$699.00 |
| 212406 | Zebra ZD421T, thermal transfer printer | \$745.00 |
| 132425 | Godex G500, 4 in direct/thermal transfer, 110/240 VAC printer | \$615.00 |
| 65617 | Label, 2.25 in × 4.5 in, direct thermal | \$17.50 |

- Zero Adjust Range:**
± 127% full scale
- Input Sensitivity:**
0.4 to 4 mV/V
- Load Cell Excitation:**
5 VDC
- Number of Scale Channels:**
One local
One remote
- Memory Items:**
100 items
- Load Cell Input Connector:**
Amphenol 14-Pin
- Computer Interface:**
RS-232 DB-9M connection
- Battery Operation:**
24 hours of continuous usage
- Charge Time:**
8 to 10 hours
- Operating Temperature:**
23 °F to 104 °F (-5 °C to 40 °C)
- Dimensions:**
(L × W × H)
14.00 × 13.75 × 4.50 in
(354 × 349 × 115 mm)

Warranty:
Two-year limited

Approvals:
NTEP 07-015
(10 to 100 lb) Class III for weigh mode only
10 to 100 lb scales only