

## PRECISION

## AD-4212A Series

## Standard Features

- Comparator output (Hi/OK/Lo) feature for manual or automatic operation as well as buzzer function
- GLP/GMP compliant software output
- Breeze break for maximum accuracy and fastest response
- Standard calibration weight
- Simple operator reference card provided
- Multi-weighing units
- Time and date clock function
- Data memory function for weighing, calibration, counting and Hi/OK/Lo values
- Super Hybrid Sensor Technology (SHS)
- WinCT<sup>©</sup> communication tools software
- RS-232 interface for connecting to printer or PC

## Specifications

## Weighing Units:

Milligram, Ounce, Carat, Pennyweight, Troy Ounce, Grain (See technical manual for complete listings)

## Operating Modes:

Counting, Percentage

## Power Supply:

120 V AC adapter, 11 VA

## Stabilization Time (typical):

AD-4212A-200, AD-4212B-201: 30 to 210 g approx. 1.0 second  
AD-4212B-301: 30 to 210 g approx. 1.0 second  
AD-4212A-600: 30 to 610 g approx. 1.1 seconds  
AD-4212A-1000: 30 to 1100 g approx. 1.1 seconds

## I/O Interface Comparator Output:

3 level output with buzzer

## I/O Interface External Contact Input:

Re-zero and print

## Calibration Weight (OIML F1) (OPT):

AD-4212A-200, AD-4212B-201, AD-4212B-301: 100 g  
AD-4212A-600, AD-4212A-1000: 200 g

## Connection Cable:

Approx. 2 m (between weighing unit and display unit)

## Operating Temperature:

41 °F to 104 °F (5 °C to 40 °C) 85% RH or less (no condensation)

## Est. Weight:

8.5 lb (4 kg)

## Warranty:

Five-year limited

## Return Policy:

A&D Weighing standard policy - restock fee may apply

Model	Capacity	Readability	Repeatability	Linearity	Pan Size	Dimensions	Part #	List Price
AD-4212A-200	210 g	1 mg	1 mg	±2 mg	2 × 2 in (50 × 50 mm)	3.2 × 9.1 × 3.5 in (80 × 230 × 90 mm)	97655	\$5,725.00
AD-4212A-600	610 g	1 mg	1 mg	±3 mg	2.8 × 2.8 in (70 × 70 mm)	3.2 × 9.1 × 3.5 in (80 × 230 × 90 mm)	97656	\$6,300.00
AD-4212A-1000	1,100 g	1 mg	1 mg	±3 mg	2.8 × 2.8 in (70 × 70 mm)	3.2 × 9.1 × 3.5 in (80 × 230 × 90 mm)	97657	\$6,550.00

## Options/Accessories

Part #	A&D Model #	Description	Price
97672	AD-4212A-01	BCD output (factory installed, four month lead time)	\$615.00
97674	AD-4212A-07	Extension cable, 3 m	\$180.00
97675	AD-4212A-08	Ethernet interface with WinCT <sup>©</sup>	\$350.00
97676	AD-4212A-19	Stainless steel breeze break (200 g only)	\$130.00

