

TS SERIES TOPLOADER WASHDOWN BALANCE

FEATURES

- Stainless steel, IP65 top housing
- Large, 18 mm LCD with backlight
- Selectable modes
- 13 units of measurement
- Mono-metal tuning fork sensor (MMTS) provides quick response and stability
- Washdown with IP65 rating
- 115 VAC adapter included (230 VAC optional)
- Semi-automatic calibration, external weight
- RS-232 interface for connecting to printer or PC

OPTIONS

- Battery holder
- Underweigh hook
- Waterproof RS-232 cable

SPECIFICATIONS

Weighing Units:

Carat, Pennyweight, Troy Ounce, Decimal Ounce, Decimal Pound (See technical manual for complete listing)

Operating Modes:

Weight, Count, Percentage, Limit Function (Checkweighing)

Power:

120 VAC (adapter included)

Battery Option:

Nickel-cadmium battery, 12-hour run time, 24-hour charge time

RS-232 Baud Rate:

1200/2400/2800/9600;
Data bits-8, Connector-DIN 5-pin

Calibration Weight:

TP-620: 600 g
TP-6200: 6,000 g
TP-8200: 8,000 g

Operating Temperature:

41 °F to 95 °F (5 °C to 35 °C)

Est. Weight:

6.2 lb (2.8 kg)

Warranty:

Five-year limited

Return Policy:

Rice Lake standard policy





TUNING FORK ENHANCED BALANCE

MODEL	CAPACITY	PART #
TS-620	620 × 0.01 g	165338
TS-6200	6,200 × 0.1 g	165339
TS-8200	8,200 × 0.1 g	165340

OPTIONS

DESCRIPTION	PART #
AC adapter, multi-range 110:230 V AC, 6 V DC	108499
9-pin D-sub F-25-Pin D-sub connector	72440
9-pin D-sub F to blunt end	22436
Null modem cable	66535
Slimline adapter, null modem gender changer	119064
Underweigh hook	109236
Waterproof RS-232 cable	109238
Additional operating manual	109050
Battery operator manual	112611
Battery holder option, requires Four AA batteries (not included)	112516
AbleCable, requires null modem cable PN 66535	119919



PN 108499 Multi-range AC adapter and multi-plug