

# **MVE XC Series**

### Large capacity storage

MVE XC Series tanks have capacities ranging from 700– 5000 straws and 210 to over 1000 vials. Manufactured to a world-class level of excellence and backed by an industry-leading 5-year vacuum warranty, these durable, lightweight units can be relied on to perform in the most demanding of environments. The XC Series offers a range of capacity depending on on the user needs. Neck size and canister dimensions vary from model to model in order to optimize the sample capacity, inventory system, or holding time for each application.

### Key Features

- Designed for largecapacity storage
- Low liquid nitrogen consumption
- o Convenient lightweight package
- XC 20 Signature includes Bend Don't Break<sup>™</sup> & Semen Safe<sup>™</sup> durability features




## **MVE XC Series**

	XC 20 Signature	XC 22/5	XC 32/8	XC 33/22	XC 34/18	XC 47/11-6	XC 47/11-10
Maximum Storage Capacity							
• Number of Canisters	6	6	9	6	6	6	10
• Number of 1/2 cc Straws 10/cane	660	2,400	2,520	1,260	2,100	4,500+	3,500
• Number of 1/2 cc Straws 1 Level Bulk	879	3,666	3,960	1,764	3,000	6,216	5,000
• Number of 1/2 cc Straws 2 Level Bulk	1,680	-	-	-	630	1,320	1,050
• Number of 1.2 & 2.0 ml Vials 5/cane	210	810	855	360	-	-	-
Performance							
• LN <sub>2</sub> Capacity L	20.5	22.4	32.0	33.4	34.8	47.4	47.4
• Static Evaporation Rate* L/day	0.090	0.35	0.35	0.14	0.18	0.39	0.39
• Normal Working Duration**, Full Days	142	40	57	154	123	76	76
Unit Dimensions							
• Neck Opening in. (mm)	2.18 (55.4)	3.81 (97)	3.81 (97)	2.75 (70)	3.50 (89)	5.00 (127)	5.00 (127)
o Overall Height in. (mm)	26.0 (660)	22.0 (559)	21.5 (546)	26.0 (660)	26.6 (675)	26.5 (673)	26.5 (673)
• Overall Inner Height in. (mm)	-	-	-	-	-	-	-
• Outer Diameter in. (mm)	14.5 (368)	14.5 (368)	18.2 (464)	18.2 (464)	18.2 (464)	20.0 (508)	20.0 (508)
• Canister Height in. (mm)	11/5 (279/127)	11 (279)	11 (279)	111 (279)	11 (279)	11 (279)	11 (279)
• Canister Diameter in. (mm)	1.65 (41.9)	3.09 (79)	2.62 (67)	2.22 (56)	2.81 (71)	4.00 (102)	2.81 (71)
• Weight Empty lb. (kg)	22 (10)	26 (11.8)	30 (13.6)	34 (15.4)	34 (15.4)	42 (19.0)	42 (19.0)
• Weight Full Ib. (kg)	58.4 (26.5)	66.0 (30)	87.0 (39.5)	94.0 (42.5)	96.0 (43.5)	120.4 (54.6)	120.4 (54.6)

#### FIVE Year Vacuum Warranty • TWO Year Parts Warranty

\* Static evaporation rate and static holding time are nominal. Actual rate and holding time will be affected by the nature of container use, atmospheric conditions, and manufacturing tolerances.

\*\* Working Duration is an arbitrary reference, to estimate container performance under normal operating conditions in liquid storage. Actual working time may vary due to current atmospheric conditions, container history, manufacturing tolerances and patterns of use.



#### **Tank Features**

- A Tamper-proof, hinged lid
- B Locking tab
- C Color-coded canister/lid numbering system
- D High strength neck tube reduces liquid nitrogen loss
- E Advanced chemical vacuum retention system
- F Insulation to provide maximum thermal performance
- G Strong, lightweight aluminum construction
- H Spider design for easy retrieval and insertion of product

ML-000020 Ver 1

© 2024 MVE Biological Solutions reserves the right to discontinue its products, or change the prices, materials, equipment, quality, descriptions, specifications and/or processes to its products at any time without prior notice and with no further obligation or consequence. All rights not expressly stated herein are reserved by us, as applicable.

