AN-ISE sc Combination Sensor for Ammonia and Nitrate



Two-in-one low maintenance sensor measures both ammonia and nitrate at the same time.

Combination Sensor for Ammonium and Nitrate

This combination sensor has the ability to measure Ammonia and Nitrate at the same time, eliminating the need for multiple sensors.

No Reagents or Sample Preparation

This sensor utilizes ion selective electrode (ISE) technology. It is designed for immersion directly in aeration basins eliminating the need for reagents and sample preparation. The sensor can be easily installed outdoors without additional housings, so it is easy to relocate to various locations.

Compensated for Significant Interferences

The sensor compensates for the most common interferences with integrated potassium and chloride electrodes within the cartridge. The compensation allows the sensor to provide accurate and reliable results.

Easy to Maintain Sensor Cartridge

The Cartrical cartridge eliminates handling and adjustment of individual electrodes because it contains four electrodes that are factory calibrated to each other. Cartridge replacement is simple: unscrew the old cartridge, plug in the new one, and the sensor is ready for measurement. The factory calibration is automatically identified after replacing the cartridge by using RFID technology.

Energy Cost Savings

The AN-ISE sc sensor can be used to optimize Nitrogen removal to facilitate reduced costs. Whether you are monitoring in a Sequencing Batch Reactor (SBR) or in a Nitrification/Denitrification process, the sensor provides visibility to real-time Ammonia and Nitrate levels, allowing you to run the blowers when needed and save energy costs.

Order Information

AN-ISE sc Sensors

LXV440.99.00002 AN-ISE sc Low Cost ISE Combination Sensor for Ammonia

and Nitrate (immersion) with RFID, 10 m cable

LXV440.99.00012 AN-ISE sc Low Cost ISE Combination Sensor for Ammonia

and Nitrate (immersion) without RFID, 10 m cable

Please note: A digital Hach SC controller is required to operate the AN-ISE sc sensor, controller is sold separately.

Mounting Hardware

LZY714.99.32320 Pole mounting hardware AN-ISE sc/A-ISE sc/N-ISE sc,

24 cm bracket, SS pole 2 m

6184900 Rail Mount Kit

LZX914.99.12400 Chain Mount Kit (PVC) for ISE sensors

Cartridge

LZY694 Cartrical Sensor Cartridge for

AN-ISE sc/A-ISE sc/N-ISE sc Sensors

Standards and Accessories

LCW895 Test Solution 1 for AN-ISE sc/A-ISE sc/N-ISE sc Sensors, 2 L
LCW896 Test Solution 2 for AN-ISE sc/A-ISE sc/N-ISE sc Sensors, 2 L

LZY720Test Cartridge for AN-ISE sc/A-ISE sc/N-ISE scLZY771Sedimenter for AN-ISE sc/A-ISE sc/N-ISE sc

LZY706 Cleaning Unit for AN-ISE sc/A-ISE sc/N-ISE sc Sensors 6860000 High Output Air Blast Cleaning System, 115 VAC

Part numbers may vary by country.

Learn More



